

N 50, BUILT-IN OVEN, 60 X 60 CM, GRAPHITE-GREY B6ACM7AG0A













Z11AB15A0 Baking tray, non-stick ceramic coated, Z11AU15A0 Universal pan, non-stick ceramic coated, Z11CR10X0 Baking and roasting grid (standard), Z11GU20X0 Glasspan, Z11TI15X0 Cliprails, Z12CB10A0 Baking tray, enamelled, Z12CL10A0 Lid for professional pan, enamelled, Z12CN10A0 Professional pan, enamelled, Z12CV10A0 Professional pan, enamelled, Z12CV10A0 Multipurpose pan, enamelled, Z13CR10X0 Baking and roasting grid (steam), Z13CV05S0 Cover Strip, Z1608BX0 Full ext rails, level independent, Z1650BE0 Half tray, Z1655CA0 Air Fry & Grill tray, Z1913X0 Baking Stone, Z19DD10X0 Steam set for ovens

Built-in oven with Hide® - the fully retracting oven door

- $\sqrt{\text{CircoTherm}^{\odot}}$ The smart hot-air function lets you bake on up to three levels at once and achieve even cooking results.
- $\sqrt{\mbox{ Hide}^{\mbox{\scriptsize 0}}}$ The unique fully disappearing oven door.
- $\sqrt{\ }$ Singlepoint Meatprobe keeps one eye constantly on the oven temperature
- $\sqrt{\,}$ Pyrolytic Self-Cleaning with Easy Clean the duo for optimal cleaning: pyrolytic after heavy use and Easy Clean for in between
- $\sqrt{\ }$ Home Connect rediscover your kitchen with our connected home appliances, from wherever you are



N 50, BUILT-IN OVEN, 60 X 60 CM, GRAPHITE-GREY B6ACM7AG0A

Heating Functions

- Oven with 8heating methods:
- Bread Baking, Full surface grill, CircoTherm® gentle, CircoTherm®, Top/bottom heating, Pizza Setting, Bottom heating, Circo-roasting
- Temperature range 30 °C 275 °C
- Cavity volume: 71 net usable litres

Hook-in racks / rails

- Number of shelf levels: 4
- Large capacity oven with shelf supports, Telescopic shelf rails available as optional accessory

Design

- Graphite-Grey Edition
- Rotary Control, Retractable control knobs
- Cavity inner surface: enamel

Cleaning

- Pyrolytic self cleaning
- EasyClean® program
- Full glass inner door safer touch door

Convenience

- White LCD display
- \bullet Electronic clock with start / stop function
- Automatic temperature proposal, automatic start, Actual temperature display, Optical temperature control, Meat probe function
- Hide®, the fully retracting oven door
- Bar handle
- Single-point meat probe
- Rapid heat-up
- Halogen lighting
- Cooling fan
- Stainless-steel fan
- Info button
- HomeConnect

Accessories

• 1 x combination grid, 1 x universal pan

Safety and Environment

- \bullet Maximum door temperature 30° C
- Automatic door lock during pyrolysis, Individual adjustable child lock, Safety switch off, Residual heat indicator, Door contact switch

Technical Info

Length of mains cable: 120 cm
Nominal voltage: 220 - 240 V
Total connected load electric: 3.6 KW

Dimensions

- Installation dimensions (HxWxD): 585 mm 595 mm x 560 mm 568 mm x 550 mm


• Please reference the built-in dimensions provided in the installation drawing



N 50, BUILT-IN OVEN, 60 X 60 CM, GRAPHITE-GREY B6ACM7AG0A

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm



A: 19.5 mm

B: Space for appliance connection 320 x 115 mm

