

N 30, SLIDEOUT RANGEHOOD, 60 CM, SILVER METALLIC
D46BR22N1A



Slideout rangehood: Fans of streamlined kitchens love this rangehood because it's invisible inside the upper cabinet

- ✓ LED Lighting: Clear illumination while you cook.
- ✓ Integrated Power Button – the rangehood automatically starts and stops when you slide it out and back in.

Z51TB1X4	Clean Air Standard odor filter (repl.)
Z51TI1X4	Clean Air Standard recirculation kit
Z54TC01X0	Standard odor filter (replacement)
Z54TS01X0	Standard recirculation kit

Typology: Pull-out
 Length electrical supply cord: 175.0 cm
 Min. required niche size for installation (HxWxD): 162mm x 526.0mm x 290mm mm
 Minimum distance above an electric cooktop: 600 mm
 Minimum distance above a gas cooktop: 650 mm
 Net weight: 8.9 kg
 Type of control: mechanical
 Number of power settings: 3
 Maximum output air extraction: 388 m³/h
 Maximum output recirculating air: 257 m³/h
 Number of lights: 2
 Noise level: 67 dB(A) re 1 pW
 Diameter of air outlet: 120 / 150 mm
 Grease filter material: Washable aluminium
 EAN code: 4242004253686
 Connection Rating: 108 W
 Fuse protection: 10 A
 Voltage: 220-240 V
 Frequency: 50 Hz
 Plug type: AU plug
 Installation typology: Built-in



N 30, SLIDEOUT RANGEHOOD, 60 CM, SILVER
METALLIC
D46BR22N1A

- Appliance width: 598 mm
- Appliance colour: silver metallic
- For installation into a 60cm wide wall cupboard
- Suitable for ducted extraction and recirculation
- Accessories required for recirculated extraction: Recirculating kit

Design

Comfort

- Automatic On/Off operation when telescopic canopy is pulled out and pushed back
- rocker switch for power and light
- 3 power levels

Cleaning

- 2 x 1.5W LED
- Colour Temperature: 3500 K
- Cassette with alu frame
- Dishwasher safe metal grease filters

Performance

- Extraction rate exhaust air according to EN 61591: max. 389 m³/h
- Noise min./max. Normal Level: 59/67 dB
- 1 single inlet horizontal, Capacitor motor

Planning and installation information

- Appliance dimensions (HxWxD): 203 x 598 x 290 mm
- Installation dimensions (HxWxD): 162 x 526 x 290 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Electrical cable length 1.75 m

Consumption Data

- Average Energy Consumption: 40.3 kWh/year
- Lighting Efficiency Class: A
- Power rating: 108 W

N 30, SLIDEOUT RANGEHOOD, 60 CM, SILVER METALLIC
D46BR22N1A



