

N 50, Wall-mounted rangehood, 90 cm, Stainless steel  
D79MH52N1



COOKING PASSION SINCE 1877



The wall-mounted rangehood: a functional design element in the kitchen.

- ✓ Extraction rate: at 730 m<sup>3</sup>/h, it quickly ensures optimal kitchen air quality.
- ✓ Especially quiet: high performance at just 55 dB.
- ✓ LED lighting: for perfect, energy-efficient illumination of the cooktop.
- ✓ Intensive speed setting with reset: automatically resets the hood to regular speed setting after 6 min.

#### Features

##### Technical Data

Color chimney : Stainless steel  
Typology : Chimney  
Approval certificates : Australia Standards, CE, Eurasian, VDE  
Length electrical supply cord (cm) : 130  
Height of the chimney (mm) : 582-908/582-1018  
Height of product, without chimney (mm) : 46  
Minimum distance above an electric hob : 550  
Minimum distance above a gas hob : 650  
Net weight (kg) : 18.468  
Type of control : Electronic  
Number of speed settings : 3-stage + 2 intensive  
Maximum output air extraction (m<sup>3</sup>/h) : 460  
Boost position output recirculating (m<sup>3</sup>/h) : 440  
Maximum output recirculating air (m<sup>3</sup>/h) : 340  
Boost position air extraction (m<sup>3</sup>/h) : 730  
Number of lights : 3  
Noise level (dB) : 55  
Diameter of air outlet (mm) : 120 / 150  
Grease filter material : Washable aluminium  
EAN code : 4242004183808  
Connection Rating (W) : 139  
Current (A) : 10  
Voltage (V) : 220-240  
Frequency (Hz) : 50; 60  
Plug type : Gardy plug w/ earthing  
Installation typology : Wall-mounted

#### Optional accessories

Z5102X1	Active carbon filter
Z5102X5	Recirculating kit



4 242004 183808

*N 50, Wall-mounted rangehood, 90 cm, Stainless steel*  
D79MH52N1

Features

- \* 90 cm Chimney hood
- \* Box slimline design
- \* For wall mounted installation
- \* Appliance colour: Stainless steel
- \* Suitable for ducted extraction and recirculation
- \* Accessories required for recirculated extraction: Recirculating kit
- \* EASY Installation
- \* Electronic controls
- \* Push button controls (3 power levels + 2 intensive levels) with 7-segment display
- \* Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 460 m<sup>3</sup>/h  
Intensive 730 m<sup>3</sup>/h
- \* Efficient BLDC brushless motor technology
- \* Automatic intensive revert setting - 6 min
- \* Automatic run on for Automatic run on - 10 min
- \* 3 x 3 Watt LED Lights
- \* Softlight with dimming function
- \* Dishwasher safe metal grease filters
- \* Saturation indicator for grease filters
- \* Noise min./max. Normal Level: 45/55 dB  
Noise max. Intensive setting: 65 dB
- \* Additional noise insulation mats for optimised sound absorption

Technical Information

- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Power rating: 139 W
- Dimensions exhaust air (HxWxD): 628-954 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 628-1064 x 900 x 500 mm
- Electrical cable length 1.3 m

N 50, Wall-mounted rangehood, 90 cm, Stainless steel  
D79MH52N1

Dimensioned drawings

