


N 90, WALL-MOUNTED CANOPY RANGEHOOD, 90 CM, STAINLESS STEEL
D96BMU5N0A



The stylish Neff canopy rangehood is modern in design and keeps up with your cooking.

- ✓ Automatic Air Sensor: Constantly adjusts the extraction rate to match the situation in the kitchen.
- ✓ Efficient Drive Motor – Quiet and energy-efficient motor for a calmer kitchen.
- ✓ Touch Control: An integrated flat surface control panel for smooth operation with a fingerswipe.
- ✓ Intensive Speed Setting: Increases the extraction rate when cooking steam is intense.
- ✓ Dimmer Function: Easily dim the light according to your mood with the touch of a finger.

Z50XP0X0	Long Life odor filter (replacement)
Z51CB12X4	Clean Air Standard recirculation kit
Z51CXC2N6	Clean Air Plus recirc. kit external
Z51CX11X6	Clean Air Plus recirculation kit
Z51FXD2N1	Long Life recirculation kit external
Z51FXJ0X5	Long Life recirculation kit
Z53CBB2X4	Clean Air Standard odor filter (repl.)
Z53XXB1X6	Clean Air Plus odor filter (replacement)
Z5861N0	Back panel stainless steel
Z5895N0	Stainless steel back panel 900 mm
Z5906N1	Chimney extension 1000 mm
Z5916N1	Chimney extension 1500 mm

Typology:	Wall-mounted
Length electrical supply cord:	130.0 cm
Height of the chimney:	582-908/568-1018 mm
Height of product, without chimney:	46 mm
Minimum distance above an electric cooktop:	600 mm
Minimum distance above a gas cooktop:	650 mm
Net weight:	18.5 kg
Type of control:	Electronic
Number of power settings:	3-stages + 2 intensive settings
Maximum output air extraction:	430 m ³ /h
Boost position output recirculating:	457 m ³ /h
Maximum output recirculating air:	353 m ³ /h
Boost position air extraction:	844 m ³ /h
Number of lights:	3
Noise level:	55 dB(A) re 1pW
Diameter of air outlet:	120 / 150 mm
Grease filter material:	Washable stainless steel
EAN code:	4242004235965
Connection Rating:	165 W
Fuse protection:	10 A
Voltage:	220-240 V
Frequency:	50; 60 Hz
Plug type:	AU plug
Installation typology:	Wall-mounted



N 90, WALL-MOUNTED CANOPY RANGEHOOD, 90
CM, STAINLESS STEEL
D96BMU5NOA

Design & Innovation

- Box brand design
- For wall mounted installation
- Appliance width: 898 mm
- Appliance colour: brushed steel
- Electronic controls with low-lift push buttons

Heating Functions

- 3 power levels + 2 intensive levels via TouchControl
- 3 power levels + 2 intensive levels
- Extraction rate according to EN 61591 ø 15 cm: max. Normal use 430 m³/h. Intensive 844 m³/h
- Noise min./max. Normal Level: 46/55 dB
- Automatic Air Sensor

Convenience

- Automatic intensive revert setting - 6 min
- Automatic run on - 10 min
- Easy to clean Innerframe
- Softlight with Dimming function
- 3 x 1.5 Watt LED Lights
- Front profile décor strip or pelmet required (not supplied with rangehood)
- Noise reduction
- Efficient BLDC-technology
- 3 x 1.5W LED
- Light Intensity: 389 lux
- Colour Temperature: 3500 K
- Saturation display for filters
- Stainless steel filter covers, dishwasher safe
- Additional noise insulation mats for optimised sound absorption
- Average Energy Consumption: 30.1 kWh/year

Technical Information

- Suitable for ducted extraction and recirculation
- Accessories required for recirculated extraction: Recirculating kit
- EASY Installation
- Dimensions recirculating with CleanAir module (HxWxD): 689 x 898 x 500mm - mounting with outer chimney
- Noise level according to EN 60704-3 und EN 60704-2-13 at max. normal use exhaust air: 55 dB(A) re 1 pW (42 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 exhaust air:
 - Max. normal use: 55dB(A) re 1 pW
 - Intensive: 69 dB(A) re 1 pW
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- with one-way flap: prevents outside air from entering your kitchen
- Max. extraction rate: 844 m³/h
- Extraction rate in recirculation mode:
 - Max. normal use: 371m³/h

- Intensive: 513 m³/h
- Extraction rate in recirculation mode: Max. normal use: 371 m³/h. Intensive: 513 m³/h
- Dimensions exhaust air (HxWxD): 614-954 x 898 x 500 mm
- Dimensions recirculating (HxWxD): 614-1064 x 898 x 500 mm
- Power rating: 165 W
- Electrical cable length 1.3 m
- Voltage: 220 - 240 V

