N 50, Built-in oven B3ACEOANOB

















Optional accessories

Z11AB15A0 Baking tray, non-stick ceramic coated

Z11CB10E0 Baking tray, grey enamelled

Z11CR10X0 Baking and roasting grid (standard)

Z11GT10X3 Glass roasting dish, 5,4l

Z11GU20X0 Glasspan

Z11TF36X0 3 level telescopic rails, full ext

Z11TI15X0 Cliprails

Z12CQ10A0 Grill tray, anthracite enamelled

Z1913X0 Baking Stone

Built-in Slide&Hide® oven with fixed handle and fully retracting oven door

- $\sqrt{\mbox{Slide\&Hide@}}$ the fully retracting oven door, unrestricted access with fixed handle.
- $\sqrt{\rm CircoTherm^{\odot}}$ the unique hot air-system for simultaneous baking and roasting on up to 3 levels

Features

Technical Data

Color / Material Front : Stainless steel

Construction type : Built-in Integrated Cleaning system : No

Required niche size for installation (HxWxD) : $585-595 \times 560-568 \times 10^{-2}$

550

Dimensions of the product (mm) : $595 \times 594 \times 548$

Control Panel Material : Glass Door Material : Glass Net weight (kg) : 34.374 Usable volume of cavity (I) : 71

Cooking method : Conventional heat, Full width grill, Hot Air, Hot air

grilling, Pizza setting First cavity material : Other Oven control : mechanical Number of interior lights : 1 Approval certificates : CE, VDE

Length of electrical supply cord (cm): 120

EAN code: 4242004225126 Number of cavities (2010/30/EC): 1 Energy efficiency class (2010/30/EC): A

Energy consumption per cycle conventional (2010/30/EC): 1.04 Energy consumption per cycle forced air convection (2010/30/EC):

0.81

Energy efficiency index (2010/30/EC) : 95.3

Connection rating (W): 2990

Current (A): 13 Voltage (V): 220-240 Frequency (Hz): 60; 50 Plug type: no plug



N 50, Built-in oven B3ACEOANOB

Features

Design

- LCD Display (White)
- Retractable control dials, Bevelled oval controls
- Cavity inner surface: Enamel grey
- Slide&Hide® with fixed handle
- Bar handle

Features

- Control panel lock
- Heating up indicator
- Interior halogen light
- Triple glazed door

Cleaning

• Full glass inner door

Programmes/functions

- 6 heating methods: CircoTherm®, Top/bottom heat, Hot air grilling, Full surface grill, CircoTherm® intensive, CircoTherm® gentle
- Cooling fan

Accessories

• 2 x combination grid, 1 x universal pan

Performance/technical information

• Energy efficiency rating (acc. EU Nr. 65/2014): A Energy consumption per cycle in conventional mode: 1.04 kwh Energy consumption per cycle in fan-forced convection mode:

0.81 kwh

Number of cavities: Main cavity Heat source: electrical Cavity volume: 71 litre

- Total connected load electric: 2.99 KW
- Temperature range 50 °C 275 °C
- Length of mains cable: 120 cm
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 595 mm x 594 mm x 548 mm
- Niche dimension (hxwxd): 585 mm - 595 mm x 560 mm - 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual