

N 50, BUILT-IN OVEN, 60 X 60 CM, GRAPHITE-GREY B5ACH7AG0



A*** ↑ D	А	
----------------	---	--

1 x combination grid, 1 x universal pan

Z11AB15A0 Baking tray, non-stick ceramic coated, Z11AU15A0 Universal pan, non-stick ceramic coated, Z11CR10X0 Baking and roasting grid (standard), Z11GU20X0 Glasspan, Z11TI15X0 Cliprails, Z12CB10A0 Baking tray, enamelled, Z12CL10A0 Lid for professional pan, enamelled, Z12CN10A0 Professional pan, enamelled, Z12CP10A0 Pizza pan, enamelled, Z12CU10A0 Multipurpose pan, enamelled, Z1365WX0 Wireless food thermometer, Z13CR10X0 Baking and roasting grid (steam), Z13CV05S0 Cover Strip, Z1608BX0 Full ext rails, level independent, Z1650BE0 Half tray, Z1655CA0 Air Fry & Grill tray, Z1913X0 Baking Stone, Z19DD10X0 Steam set for ovens, Z99RX70X0 Connecting cable 3m

Built-in oven with Slide&Hide $^{\odot}$ - unrestricted access to the oven interior

- $\sqrt{\rm Slide\&Hide^{tot}}$ The fully disappearing oven door with rotating handle.
- $\sqrt{\rm CircoTherm^{\odot}}$ Smart hot-air solution that lets you bake on up to three levels at once.
- \checkmark Dual cleaning options: Pyrolytic cleaning programmes just let the oven interior clean itself. EasyClean the quick and easy option for day to day maintenance.
- $\sqrt{\rm LCD-Display}$ simple, straightforward with large characters for clear reading
- \checkmark Life changes, so do the design trends. The most intimate corner of your home not only should make you feel good but look great too.

Built-in / Free-standing:Built-in				
Integrated Cleaning system: Pyrolytic+Hydrolytic	2			
Required niche size for installation (HxWxD): 585-595 x 560-568 x				
550 mm				
Dimensions:	ı			
Dimensions of the packed product (HxWxD): . 660 x 660 x 690 mm				
Control Panel Material:	s			
Door Material:	5			
Net weight:	7			
Usable volume of cavity:	l			
Cooking method: Bread Baking Setting, Full width grill, Hotair				
gentle, Hot Air, Conventional heat, Pizza setting, Bottom heat, Hot				
air grilling				
Oven control: electronic	c			
Number of interior lights: 1	l			
Length electrical supply cord: 120.0 cm	ı			
EAN code:	l			
Number of cavities (2010/30/EC): 1	l			
Energy efficiency rating: A	4			
Energy consumption per cycle conventional (2010/30/EC): 1.04				
kWh/cycle				
Energy consumption per cycle forced air convection				
(2010/30/EC): 0.81 kWh/cycle				
Energy efficiency index (2010/30/EC):95.3 %	ò			
Connection Rating:	/			
Fuse protection:	ł			
Voltage:	/			
Frequency:	Z			
Plug type: no plug				
(electrical connection by electrician), Gardy plug w/ earthing				
Included accessories:1 x combination grid, 1 x universal par	۱			





N 50, BUILT-IN OVEN, 60 X 60 CM, GRAPHITE-GREY B5ACH7AG0

Features

- Oven with 8 cooking functions:, 8 cooking functions: heating methods: CircoTherm[®], Top/bottom heat, Circo-roasting, Full surface grill, CircoTherm[®] intensive, Bread baking, Bottom heat, CircoTherm[®] gentle
- Temperature range 30 °C 275 °C
- Cavity volume: 71 litre

Level independent telescopic rails

- 4 shelf positions
- Available as an accessory

Design

- Graphite-Grey Edition
- Elongated designed dials, Retractable control dials, Bevelled oval controls
- Cavity inner surface: enamel anthracite

Cleaning

- Pyrolytic cleaning
- EasyClean
- Full glass inner door

Programmes/functions

- LCD-Display Control (white)
- Electronic clock timer
- Temperature proposal
- Actual temperature display Heating up indicator Automatic start
- Slide&Hide[®] with fixed handle
- Slide&Hide[®] with rotating handle
- Rapid heat
- Interior halogen light, On/off button
- Cooling fan
- Stainless-steel fan
- Info button
- 1 x combination grid, 1 x universal pan

Features

- 30 °C Very low door temperature
- Door lock during pyrolytic cleaning
- Control panel lock Automatic safety switch off Residual heat indicator

Technical information

- 120 cm Cable length
- Nominal voltage: 220 240 V
- Total connected load electric: 3.6 KW
- Energy efficiency rating (acc. EU Nr. 65/2014): A
- Energy consumption per cycle in conventional mode:1.04 kWh
- \bullet Energy consumption per cycle in fan-forced convection mode:0.81 kWh
- Number of cavities: Main cavity Heat source: electrical Cavity volume:71 litre

Performance/technical information


- Appliance dimension (hxwxd): 595 mm x 594 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual
- We recommend you to choose complementary products within N50, in order to assure an optimal design combination of your Built-In appliances.





N 50, BUILT-IN OVEN, 60 X 60 CM, GRAPHITE-GREY B5ACH7AG0

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness		
	fitted	flush	
Induction hob	37 mm	38 mm	
Full surface Induction hob	47 mm	48 mm	
Gas hob	30 mm	38 mm	
Electric hob	27 mm	30 mm	










Installation with a hob.



measurements in mm