

N 90, Canopy cooker hood, 70 cm, clear glass black printed
D57ML67N0B



COOKING PASSION SINCE 1877



Canopy hood: designed to fit neatly under an overhead unit or cabinet. They're discreet and effectively use valuable space.

- ✓ LED lighting: a clear illumination whilst cooking thanks to the energy-saving LED lights
- ✓ Dimmer Function – easily dim the light according to your mood with the touch of a finger
- ✓ EfficientDrive: save energy and enjoy a quieter kitchen thanks to efficient brushless motor technology
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ High extraction rate: Ensures a clear view while cooking thanks to efficient motor technology as either a ducted or recirculating solution.

A



Features

Technical Data

Typology : Traditional
 Approval certificates : Australia Standards, CE, VDE
 Length of electrical supply cord (cm) : 150
 Required niche size for installation (HxWxD) : 418mm x 676.0mm x 264mm
 Minimum distance above an electric hob : 500
 Minimum distance above a gas hob : 650
 Net weight (kg) : 10.170
 Type of control : Electronic
 Maximum output air extraction (m³/h) : 575
 Boost position output recirculating (m³/h) : 370.0
 Boost position air extraction (m³/h) : 775
 Number of lights (Stck) : 2
 Noise level (dB(A) re 1 pW) : 65
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Washable aluminium
 EAN code : 4242004187783
 Connection rating (W) : 272
 Current (A) : 3
 Voltage (V) : 220-240
 Frequency (Hz) : 50
 Plug type : GB plug
 Installation type : Built-in

Optional accessories

Z5100X0	Remote control
Z5135X1	Standard odor filter (replacement)
Z5135X3	Standard recirculation kit
Z511TPOX0	Long Life odor filter (replacement)
Z54TR60X3	CleanAir Recirculation Kit



4 242004 187783

*N 90, Canopy cooker hood, 70 cm, clear glass black
printed
D57ML67NOB*

Features

Features

- For installation in a kitchen cabinet
- LED display
- 2 x 1W LED lights
- softLight with dimmer function
- 2 metal grease filter cassettes
- Saturation indicator for grease filter
- Filter cover glass, metal grease filter
- Interval operation
- 3 speeds plus intensive
- Automatic after running (30 mins)
- Automatic intensive revert (6mins)
-
- EfficientDrive BLDC technology
- Rim ventilation

Design

- Stainless steel
- Stainless steel
- Canopy hood
-
- Soft touch control
- Electronic controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- In recirculation operation chimless use possible
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 575 m³/h
Intensive 775 m³/h
- Power rating: 272 W
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 65 dB (A) re 1pW
- Noise max. Normal Level: 65 dB*
- Light Intensity: 244 lux
- Colour Temperature: 4000 K
- Electrical cable length 1.5 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 418-418 x 700 x 300 mm
- Dimensions recirculating (HxWxD): 418-418 x 700 x 300 mm
- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*
- Average Energy Consumption: 46.6 kWh/year*

Optional accessories

- Recirculating kit Z5135X1
- Max. extraction rate: 775 m³/h
- Dimensions (HxWxD): 418 x 700 x 300 mm

* In accordance with the EU-Regulation No 65/2014