# N 50, Wall-mounted cooker hood, 60 cm, clear glass D64GFM1N0B





## The flat glass canopy hood accentuates the box hood design with a mix of modern materials and straight lines.

- $\sqrt{}$  TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- $\checkmark\,$  Intensive speed setting: increases the extraction rate when the steam gets intense
- $\checkmark\,$  LED lighting: a clear illumination whilst cooking thanks to the energy-saving LED lights
- $\checkmark\,$  Reduced Noise: the low-noise motor makes it possible to listen to your own kitchen story

#### Features

Technical Data Typology : Chimney Approval certificates : CE, VDE Length of electrical supply cord (cm) : 130 Height of the chimney (mm) : 576-906/576-998 Height of product, without chimney (mm) : 59 Minimum distance above an electric hob : 550 Minimum distance above a gas hob : 650 Net weight (kg) : 14.082 Type of control : Electronic Maximum output air extraction (m3/h) : 384 Boost position output recirculating (m3/h) : 358.0 Maximum output recirculating air (m3/h) : 289 Boost position air extraction (m<sup>3</sup>/h) : 626 Number of lights (Stck) : 2 Noise level (dB(A) re 1 pW) : 62 Diameter of air outlet (mm) : 120 / 150 Grease filter material : Washable aluminium EAN code : 4242004224075 Connection rating (W) : 220 Current (A) : 10 Voltage (V) : 220-240 Frequency (Hz) : 50; 60 Plug type : GB plug Installation type : Wall-mounted



#### Optional accessories

Z50XXP0X0 : Long Life odor filter (replacement) , Z51DXA0X0 : Standard odor filter (replacement) , Z51DXI1X6 : Clean Air Plus recirculation kit , Z51DXU0X0 : Standard recirculation kit , Z51FXC1N6 : Clean Air Plus recirc. kit external , Z51FXD1N1 : Long Life recirculation kit external , Z51FXJ0X0 : Long Life recirculation kit , Z53XXB1X6 : Clean Air Plus odor filter (replacement) , Z5860N0 : Back panel stainless steel , Z5865N0 : Stainless steel back panel 600 mm , Z5905N0 : Chimney extension 1000 mm , Z5915N0 : Chimney extension 1500 mm

### N 50, Wall-mounted cooker hood, 60 cm, clear glass D64GFM1N0B



#### Features

#### Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm: max. Normal use 384 m<sup>3</sup>/h Intensive 626 m<sup>3</sup>/h
- $\bullet$  Noise max. Normal Level: Noise, max. speed in normal us: 62 dB dB\*

#### Features

- Touch control
- LED display
- 3 speeds plus intensive
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 1 metal grease filter cassette
- For wall mounted installation

#### Design

- Chimney hood
- Electronic controls

#### Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Max. extraction rate: 626 m3/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 62 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 62 dB(A) re 1 pW Intensive: 70 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 62 dB (A) re 1pW
- Extraction rate in recirculation mode: Max. normal use: 289 m<sup>3</sup>/h Intensive: 358 m<sup>3</sup>/h
- Noise levels in recirculation mode: Max. normal use: 71 dB(A) re 1 pW Intensive: 75 dB(A) re 1 pW
- Power rating: 220 W
- Light Intensity: 281 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 600 x 525 mm
- Dimensions recirculating (HxWxD): 635-1075 x 600 x 525 mm
- Dimensions recirculating with CleanAir module (HxWxD): 703 x 600 x 525 mm - mounting with outer chimney 833-1163 x 600 x 525 mm - mounting with telescopic chimney
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Average Energy Consumption: 47.4 kWh/year\*

Optional accessories

- Recirculating kit Z50XXP0X0
- \* In accordance with the EU-Regulation No 65/2014

N 50, Wall-mounted cooker hood, 60 cm, clear glass D64GFM1N0B



