

N 30, INTEGRATED COOKER HOOD, 60 CM, SILVER  
D64MAC1X0B



B

Optional accessories

Z51IMA0X0 Standard odor filter (replacement)

The Integrated Cooker Hood with a fold out unit is discreetly hidden within the upper cabinets.

✓ LED Lighting – Clear illumination while you cook.

Features

Technical Data

Typology: ..... Built-in/Built-under  
 Length electrical supply cord: ..... 150.0 cm  
 Minimum distance above an electric hob: ..... 500 mm  
 Minimum distance above a gas hob: ..... 650 mm  
 Net weight: ..... 10.8 kg  
 Type of control: ..... mechanical  
 Number of speed settings: ..... 3  
 Maximum output air extraction: ..... 625 m<sup>3</sup>/h  
 Maximum output recirculating air: ..... 416 m<sup>3</sup>/h  
 Maximum Air flow: ..... 625 m<sup>3</sup>/h  
 Number of lights: ..... 2  
 Noise level: ..... 70 dB(A) re 1 pW  
 Diameter of air outlet: ..... 150 / 120 mm  
 Grease filter material: ..... Washable aluminium  
 EAN code: ..... 4242004223375  
 Connection Rating: ..... 256 W  
 Fuse protection: ..... 10 A  
 Voltage: ..... 220-240 V  
 Frequency: ..... 50; 60 Hz  
 Plug type: ..... GB plug  
 Installation typology: ..... Wall-mounted



## N 30, INTEGRATED COOKER HOOD, 60 CM, SILVER D64MAC1X0B

### Features

#### Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 625 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 70 dB dB\*

#### Features

- Push button control operation
- 3 power levels
- 2 x 3W LED
- Single motor
- 2 metal grease filter cassettes

#### Design

- Integrated hood
- Installation: Between Cupboards
- Hinged door
- Mechanical controls

#### Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction charcoal filter (accessory) needed
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 70 dB(A) re 1 pW
- Power rating: 256 W
- Light Intensity: 188 lux
- Colour Temperature: 2700 K
- Electrical cable length 1.5 m
- Blower Efficiency Class: B\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: C\*
- Average Energy Consumption: 68.4 kWh/year\*
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 402-402 x 599 x 271 mm
- Dimensions recirculating (HxWxD): 402-402 x 599 x 271 mm

#### Optional accessories

- Recirculating kit Z51IMA0X0

\* In accordance with the EU-Regulation No 65/2014

N 30, INTEGRATED COOKER HOOD, 60 CM, SILVER  
D64MAC1X0B

Dimensioned drawings

