

N 70, Integrated Design Hood, 60 cm, White with LED backlit
glass panel
D64XAF8NOB



B

Our invisible integrated design hood - perfectly integrated with extra storage for easy access items, such as spices and herbs.

✓ LED Lighting – Clear illumination while you cook.

Features

Technical Data

Typology : Built-in/Built-under
 Length of electrical supply cord : 150 cm
 Min. required niche size for installation (HxWxD) : 356mm x 562.0mm x 310mm mm
 Minimum distance above an electric hob : 500 mm
 Minimum distance above a gas hob : 650 mm
 Net weight : 11.3 kg
 Type of control : mechanical
 Number of speed settings : 3
 Maximum output air extraction : 610 m³/h
 Maximum output recirculating air : 573 m³/h
 Number of lights (Stck) : 2
 Noise level : 70 dB(A) re 1 pW
 Diameter of air outlet : 150 mm
 Grease filter material : Washable aluminium
 EAN code : 4242004243618
 Connection rating : 255 W
 Voltage : 220-240 V
 Frequency : 50; 60 Hz
 Plug type : Euro plug w/ earthing 16A/250V
 Installation type : Built-in



4 242004 243618

Optional accessories

Z51IBG0N1 Chimney extension 120mm
 Z51IBN0N0 Chimney extension 187-360mm
 Z51IBU0X0 Standard recirculation kit
 Z51IMA0X0 Standard odor filter (replacement)
 Z51ITD1X1 Long Life recirculation kit external
 Z51IXB1X6 Clean Air Plus odor filter (replacement)
 Z51IXC1X6 Clean Air Plus recirc. kit external

*N 70, Integrated Design Hood, 60 cm, White with
LED backlit glass panel
D64XAF8NOB*

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 610 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 70 dB dB*

Features

- 3 power levels via rotary switch, retractable
- White with LED backlit glass panel
- 2 x LED 2.5W
- Colour Temperature: 3500 K
- Filter cover glass, metal grease filter
- 1 metal grease filter cassette
- Installation: Cupboard 60 cm

Design

- Adjustable glass visor for additional vapour capture
- Filler strip for an individual depth adjustment in cupboard up to maximum 350 mm.
- Mechanical controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Max. extraction rate: 610 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 70 dB(A) re 1 pW
- Power rating: 255 W
- Light Intensity: 76 lux
- Electrical cable length 1.5 m
- Diameter pipe Ø 150 mm (Ø 150 mm enclosed)
- Dimensions (HxWxD): 356 x 594 x 310 mm
- Built-in dimensions (HxWxD): 356 x 562 x 310-350 mm
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 61 kWh/year*

Optional accessories

- Recirculating kit Z51IBUOX0

* In accordance with the EU-Regulation No 65/2014

N 70, Integrated Design Hood, 60 cm, White with
LED backlit glass panel
D64XAF8NOB

Dimensioned drawings

