

N 30, WALL-MOUNTED COOKER HOOD, 80 CM,  
CLEAR GLASS BLACK PRINTED  
D831DK1S0B



A

#### Optional accessories

Z51GIA1X3	Standard odor filter (replacement)
Z51GIU1X3	Standard recirculation kit

The Inclined Hood with low-noise motor and Touch Control for an odor- and noise-free kitchen.

- ✓ Reduced Noise: our optimised motor guarantees a quiet cooking experience.
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ Touch Control: an integrated flat surface control panel for smooth operation with a fingerswipe.
- ✓ LED Lighting – Clear illumination while you cook.

#### Features

#### Technical Data

Typology: .....	Wall-mounted
Length electrical supply cord: .....	150.0 cm
Height of the appliance: .....	325 mm
Minimum distance above an electric hob: .....	450 mm
Minimum distance above a gas hob: .....	650 mm
Net weight: .....	11.7 kg
Type of control: .....	Electronic
Number of speed settings: .....	3-stages + intensive setting
Maximum output air extraction: .....	430 m <sup>3</sup> /h
Boost position output recirculating: .....	550.0 m <sup>3</sup> /h
Maximum output recirculating air: .....	445 m <sup>3</sup> /h
Boost position air extraction: .....	550 m <sup>3</sup> /h
Maximum Air flow: .....	430 m <sup>3</sup> /h
Number of lights: .....	2
Noise level: .....	60 dB(A) re 1 pW
Diameter of air outlet: .....	150 mm
Grease filter material: .....	Washable aluminium
EAN code: .....	4242004273332
Connection Rating: .....	223 W
Fuse protection: .....	4 A
Voltage: .....	220-240 V
Frequency: .....	50 Hz
Plug type: .....	GB plug
Installation typology: .....	Wall-mounted



N 30, WALL-MOUNTED COOKER HOOD, 80 CM,  
CLEAR GLASS BLACK PRINTED  
D83IDK1SOB

## Features

### Design:

- Inclined glass common design
- wall-mounted
- Black glass
- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit (accessory) needed

### Core Features:

- Capacitor motor
- 2 x LED lights
- Colour Temperature: 4000 K
- Light Intensity: 127 lux
- 1 metal grease filter(s).

### Comfort Features:

- Electronic control via Touch control, backlighted
- 3 speeds plus intensive
- Automatic reset from intensive to normal setting after 5 min.
- Saturation indicator for metal and charcoal filter

### Cleaning Comfort:

- Large opening angle of the glass plate with locking function for an easy filter accessibility and easy cleaning.
- Easy to clean smooth surfaces and materials.
- metal grease filter dishwasher-safe

### Performance Exhaust:

- According to EN 61591 and EN/ IEC 60704-2-13 your appliance can achieve the following values in exhaust mode: Speed 1: extraction rate 220 m<sup>3</sup>/h; noise level 46 dB (A) re1pW Speed 2: extraction rate 315 m<sup>3</sup>/h; noise level 53 dB (A) re1pW Speed 3: extraction rate 430 m<sup>3</sup>/h; noise level 60 dB (A) re1pW Intensive 1: extraction rate 550 m<sup>3</sup>/h; noise level 65 dB (A) re1pW

### Performance Recirculation:

- According to EN 61591 and EN/ IEC 60704-2-13 your appliance can achieve the following values in recirculation mode with standard recirculation kit (available as optional accessory): Speed 1: extraction rate 215 m<sup>3</sup>/h; noise level 51 dB (A) re1pW Speed 2: extraction rate 300 m<sup>3</sup>/h; noise level 61 dB (A) re1pW Speed 3: extraction rate 445 m<sup>3</sup>/h ; noise level 69 dB (A) re1pW Intensive Speed 1: extraction rate 550 m<sup>3</sup>/h; noise level 72 dB (A) re1pW

### Technical Information and Sustainability:

- Consumption data:
- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Average Energy Consumption: 43.8 kWh/year\*
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: E\*
- Power rating: 223 W
- Voltage: Nominal voltage: 220 - 240 V

### Planning and Installation Information:

- Dimensions exhaust air (HxWxD): 690-900 x 790 x 325 mm
- Dimensions recirculating (HxWxD): 720-975 x 790 x 325 mm
- Diameter pipe Ø 150 mm (Ø 150 mm enclosed)
- Electrical cable length 1.5 m
- Back-pressure flap: Yes

N 30, WALL-MOUNTED COOKER HOOD, 80 CM,  
CLEAR GLASS BLACK PRINTED  
D83IDK1SOB

Dimensioned drawings

