

N 50, Wall-mounted cooker hood, 90 cm, clear glass  
D94GFM1NOB



COOKING PASSION SINCE 1877



The flat glass canopy hood accentuates the box hood design with a mix of modern materials and straight lines.

- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ LED lighting: a clear illumination whilst cooking thanks to the energy-saving LED lights
- ✓ Reduced Noise: the low-noise motor makes it possible to listen to your own kitchen story

#### Features

##### Technical Data

Typology : Chimney  
Approval certificates : CE, VDE  
Length of electrical supply cord (cm) : 130  
Height of the chimney (mm) : 576-906/576-998  
Height of product, without chimney (mm) : 59  
Minimum distance above an electric hob : 550  
Minimum distance above a gas hob : 650  
Net weight (kg) : 19.374  
Type of control : Electronic  
Maximum output air extraction (m<sup>3</sup>/h) : 388  
Boost position output recirculating (m<sup>3</sup>/h) : 364.0  
Maximum output recirculating air (m<sup>3</sup>/h) : 303  
Boost position air extraction (m<sup>3</sup>/h) : 636  
Number of lights (Stck) : 2  
Noise level (dB(A) re 1 pW) : 61  
Diameter of air outlet (mm) : 120 / 150  
Grease filter material : Washable aluminium  
EAN code : 4242004224204  
Connection rating (W) : 220  
Current (A) : 10  
Voltage (V) : 220-240  
Frequency (Hz) : 50; 60  
Plug type : GB plug  
Installation type : Wall-mounted

#### Optional accessories

Z50XPOX0 : Long Life odor filter (replacement) , Z51DXA0X0 : Standard odor filter (replacement) , Z51DXI1X6 : Clean Air Plus recirculation kit , Z51DXU0X0 : Standard recirculation kit , Z51FXC1N6 : Clean Air Plus recirc. kit external , Z51FXD1N1 : Long Life recirculation kit external , Z51FXJ0X0 : Long Life recirculation kit , Z53XXB1X6 : Clean Air Plus odor filter (replacement) , Z5861N0 : Back panel stainless steel , Z5895N0 : Stainless steel back panel 900 mm , Z5905N0 : Chimney extension 1000 mm , Z5915N0 : Chimney extension 1500 mm



4 242004 224204

N 50, Wall-mounted cooker hood, 90 cm, clear  
glass  
D94GFM1NOB



COOKING PASSION SINCE 1877

## Features

### Key performance features:

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 388 m<sup>3</sup>/h  
Intensive 636 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 61 dB dB\*

### Features

- Touch control
- LED display
- 3 speeds plus intensive
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- For wall mounted installation

### Design

- Chimney hood
- Electronic controls

### Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Max. extraction rate: 636 m<sup>3</sup>/h
- Extraction rate in recirculation mode:  
Max. normal use: 303 m<sup>3</sup>/h  
Intensive: 364 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 61 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:  
Max. normal use: 61 dB(A) re 1 pW  
Intensive: 69 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 61 dB (A) re 1pW
- Noise levels in recirculation mode:  
Max. normal use: 71 dB(A) re 1 pW  
Intensive: 75 dB(A) re 1 pW
- Power rating: 220 W
- Light Intensity: 214 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 900 x 525 mm
- Dimensions recirculating (HxWxD): 635-1075 x 900 x 525 mm
- Dimensions recirculating with CleanAir module (HxWxD):  
703 x 900 x 525 mm - mounting with outer chimney  
833-1163 x 900 x 525 mm - mounting with telescopic chimney
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Average Energy Consumption: 43 kWh/year\*

### Optional accessories

- Recirculating kit Z50XXPOX0

\* In accordance with the EU-Regulation No 65/2014

N 50, Wall-mounted cooker hood, 90 cm, clear glass  
D94GFM1NOB

## Dimensioned drawings

