


N 90, Wall-mounted cooker hood, 90 cm, clear glass black printed
D95FMW1NOB



B



The high-powered flat slimline hood with a flat front panel ensures you have enough space to get close to your cooking

- ✓ Oven fit: bring harmony to your kitchen
- ✓ Ambient Light – Individualized lighting with endless colour shades via Home Connect.
- ✓ Fully Automatic Hood – Takes control as soon as you switch on the hob.
- ✓ Cooktop-based Hood Control – Adjust your hood's extraction level and lighting.
- ✓ Efficient Drive Motor – Quiet and energy-efficient hood motor for a calmer kitchen.

Features

Technical Data

Typology : Wall-mounted
 Approval certificates : CE, VDE
 Length of electrical supply cord : 130 cm
 Height of product, without chimney : 430 mm
 Minimum distance above an electric hob : 450 mm
 Minimum distance above a gas hob : 650 mm
 Net weight : 23.2 kg
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction : 394 m³/h
 Boost position output recirculating : 404 m³/h
 Maximum output recirculating air : 249 m³/h
 Boost position air extraction : 717 m³/h
 Number of lights (Stck) : 2
 Noise level : 57 dB(A) re 1 pW
 Diameter of air outlet : 120 / 150 mm
 Grease filter material : Washable aluminium
 EAN code : 4242004244509
 Connection rating : 150 W
 Fuse protection : 10 A
 Voltage : 220-240 V
 Frequency : 50; 60 Hz
 Plug type : GB plug
 Installation type : Wall-mounted

Optional accessories

Z51AF1X6 Clean Air Plus recirculation kit
 Z51AFR0X0 Long Life recirculation kit (chimless)
 Z51AFS0X0 Long Life recirculation kit
 Z51AFV1X6 Clean Air Plus recirc. kit (chimless)
 Z51AXK0N0 Chimney extension 1000 mm
 Z51AXL0N0 Chimney extension 1500 mm
 Z53XXB1X6 Clean Air Plus odor filter (replacement)
 Z91AXE1S1 Chimney standard black



*N 90, Wall-mounted cooker hood, 90 cm, clear
glass black printed
D95FMW1NOB*



COOKING PASSION SINCE 1877

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 394 m³/h
Intensive 717 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 57 dB dB*

Special features

- Climate Control Sensor
- Additional functions: Ambient light RGB
- Hob-Hood control (with Wi-Fi enabled hob)
- Remote Monitoring and Control for connected home appliances and operation via smartphone or tablet (only in countries where Home Connect service is available)
- The Home Connect functionality can be extended by integrating numerous applications from external cooperation partners (partnerships)
- Voice Control enabled via popular voice assistants (only in countries where this service is available)
- Fully automatic hood

Features

- Touch control
- LED display
- 3 power levels and 2 intensive settings
- 2 x 3w LED Light
- Colour Temperature: 3500 K
- softLight with dimmer function
- Noise reduction function
- Interval operation
- Automatic after running (Automatic after running (10 minutes))
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- easy to clean Inner frame
- Installation: wall
- Rim ventilation

Design

- Chimney hood
- Electronic controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Installation system: Wall fixing inclined/flat/cube
- Extraction rate according to EN 61591 max. 717 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 57 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 57 dB(A) re 1 pW
Intensive: 70 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 57 dB (A) re 1pW
- Extraction rate in recirculation mode:
Max. normal use: 311 m³/h
Intensive: 578 m³/h
- Noise levels in recirculation mode:
Max. normal use: 60 dB(A) re 1 pW
Intensive: 74 dB(A) re 1 pW
- Power rating: 150 W
- Light Intensity: 589 lux
- Electrical cable length 1.3 m
- Diameter pipe \varnothing 150 mm (\varnothing 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 969-1239 x 895 x 263 mm
- Dimensions recirculating (HxWxD): 1029-1299 x 895 x 263 mm
- Dimensions recirculating with CleanAir module (HxWxD):
1159 x 895 x 263 mm - mounting with outer chimney
1229-1499 x 895 x 263 mm - mounting with telescopic chimney
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 40 kWh/year*

Optional accessories

- Recirculating kit Z50XXPOX0

* In accordance with the EU-Regulation No 65/2014

N 90, Wall-mounted cooker hood, 90 cm, clear glass black printed
D95FMW1N0B

Dimensioned drawings

