# N 70, WALL-MOUNTED COOKER HOOD, 90 CM, CLEAR GLASS BLACK PRINTED
# D95FRM1S0B

A

Efficient Silent Drive

The Creative Slimline hood does not only offer high-performance but is also magnetic, can be written on and can be used as a bookshelf

- √ Efficient Drive Motor – Quiet and energy-efficient hood motor for a calmer kitchen.
- √ Touch Control: an integrated flat surface control panel for smooth operation with a fingerswipe.
- √ Intensive speed setting: increases the extraction rate when the steam gets intense
- √ LED Lighting – Clear illumination while you cook.

## Optional accessories

| | |
|---|---|
| Z50XXP0X0 | Long Life odor filter (replacement) |
| Z51AFB1X6 | Clean Air Plus odor filter (replacement) |
| Z51AFI1X6 | Clean Air Plus recirculation kit |
| Z51AFR0X0 | Long Life recirculation kit (chimless) |
| Z51AFS0X0 | Long Life recirculation kit |
| Z51AFV1X6 | Clean Air Plus recirc. kit (chimless) |
| Z51AXC1N6 | Clean Air Plus recirc. kit external |
| Z51AXK0N0 | Chimney extension 1000 mm |
| Z51AXL0N0 | Chimney extension 1500 mm |
| Z53XXB1X6 | Clean Air Plus odor filter (replacement) |
| Z91AXE1S1 | Chimney standard black |

## Features

### Technical Data

Typology: ..... Wall-mounted
Length electrical supply cord: ..... 130.0 cm
Height of the appliance: ..... 430 mm
Minimum distance above an electric hob: ..... 450 mm
Net weight: ..... 22.7 kg
Type of control: ..... Electronic
Number of speed settings: ..... 3-stages + intensive setting
Maximum output air extraction: ..... 405 m³/h
Boost position output recirculating: ..... 404 m³/h
Maximum output recirculating air: ..... 249 m³/h
Boost position air extraction: ..... 739 m³/h
Maximum Air flow: ..... 405 m³/h
Number of lights: ..... 2
Noise level: ..... 58 dB(A) re 1 pW
Diameter of air outlet: ..... 120 / 150 mm
Grease filter material: ..... Washable aluminium
EAN code: ..... 4242004210177
Connection Rating: ..... 143 W
Fuse protection: ..... 10 A
Voltage: ..... 220-240 V
Frequency: ..... 60; 50 Hz
Plug type: ..... GB plug
Installation typology: ..... Wall-mounted

4 242004 210177

# N 70, WALL-MOUNTED COOKER HOOD, 90 CM, CLEAR GLASS BLACK PRINTED D95FRM1S0B

## Features

**Key performance features:**

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use404m³/h
- Intensive739 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 58 dB dB*

**Features**

- Touch control
- LED display
- 3 speeds plus intensive
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- easy to clean Inner frame
- Installation: wall
- Rim ventilation

**Design**

- Chimney hood
- Electronic controls

**Performance/technical information**

- Installation with gas hob not recommended
- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Installation system: Wall fixing inclined/flat/cube
- Extraction rate according to EN 61591 max. 739 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 58 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use:58dB(A) re 1 pW
- Intensive:71 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1pW
- Power rating: 143 W
- Light Intensity: 225 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 981-1251 x 890 x 362 mm
- Dimensions recirculating (HxWxD): 1041-1311 x 890 x 362 mm
- Dimensions recirculating with CleanAir module (HxWxD):
- 1171 x 890 x 362mm - mounting with outer chimney
- 1241-1511 x 890 x 362 mm - mounting with telescopic chimney
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 39 kWh/year*

**Optional accessories**

- Recirculating kit Z50XXP0X0

* In accordance with the EU-Regulation No 65/2014

# N 70, WALL-MOUNTED COOKER HOOD, 90 CM, CLEAR GLASS BLACK PRINTED
D95FRM1S0B

## Dimensioned drawings




(1) Exhaust air
(2) Circulated air
(3) Air outlet – slot for exhaust air mounted facing down

measurements in mm




Appliance in circulated air mode without duct
Circulated air set required

measurements in mm




measurements in mm




(1)Position of socket

Note the maximum thickness of the back panel.

measurements in mm

## Dimensioned drawings