


N 90, Wall-mounted cooker hood, 90 cm, clear glass black printed  
D951MT1N0B



A



The design hood with an inclined front and high power ensures headroom while cooking.

- ✓ Oven fit: bring harmony to your kitchen
- ✓ Ambient Light – Individualized lighting with endless colour shades via Home Connect.
- ✓ Efficient Drive Motor – Quiet and energy-efficient hood motor for a calmer kitchen.
- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense

#### Features

##### Technical Data

Typology : Wall-mounted  
 Approval certificates : CE, VDE  
 Length of electrical supply cord : 130 cm  
 Height of product, without chimney : 323 mm  
 Minimum distance above an electric hob : 450 mm  
 Minimum distance above a gas hob : 650 mm  
 Net weight : 22.7 kg  
 Type of control : Electronic  
 Number of speed settings : 3-stage + 2 intensive  
 Maximum output air extraction : 431 m<sup>3</sup>/h  
 Boost position output recirculating : 632.0 m<sup>3</sup>/h  
 Maximum output recirculating air : 410 m<sup>3</sup>/h  
 Boost position air extraction : 714 m<sup>3</sup>/h  
 Number of lights (Stck) : 2  
 Noise level : 53 dB(A) re 1 pW  
 Diameter of air outlet : 150 / 120 mm  
 Grease filter material : Washable aluminium  
 EAN code : 4242004230786  
 Connection rating : 147 W  
 Fuse protection : 10 A  
 Voltage : 220-240 V  
 Frequency : 50; 60 Hz  
 Plug type : GB plug  
 Installation type : Wall-mounted

#### Optional accessories

Z51AII1X6	Clean Air Plus recirculation kit
Z51AIROX0	Long Life recirculation kit (chimless)
Z51AISOX0	Long Life recirculation kit
Z51AIV1X6	Clean Air Plus recirc. kit (chimless)
Z51AXK0N0	Chimney extension 1000 mm
Z51AXL0N0	Chimney extension 1500 mm
Z53XXB1X6	Clean Air Plus odor filter (replacement)
Z91AXE1S1	Chimney standard black



4 242004 230786

N 90, Wall-mounted cooker hood, 90 cm, clear  
glass black printed  
D951MT1NOB



COOKING PASSION SINCE 1877

## Features

### Key performance features:

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:  
max. Normal use 431 m<sup>3</sup>/h  
Intensive 714 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 53 dB dB\*

### Features

- Additional functions: Ambient light RGB
- Touch control
- LED display
- 3 power levels and 2 intensive settings
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- softLight with dimmer function
- Efficient BLDC-technology
- Noise reduction function
- Interval operation
- Automatic after running (Automatic after running (10 minutes))
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- easy to clean Inner frame
- Installation: wall
- Rim ventilation

### Design

- Chimney hood
- Electronic controls

### Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Installation system: Wall fixing inclined/flat/cube
- Extraction rate according to EN 61591 max. 714 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 53 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:  
Max. normal use: 53 dB(A) re 1 pW  
Intensive: 65 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 53 dB (A) re 1pW
- Extraction rate in recirculation mode:  
Max. normal use: 410 m<sup>3</sup>/h  
Intensive: 632 m<sup>3</sup>/h
- Noise levels in recirculation mode:  
Max. normal use: 63 dB(A) re 1 pW  
Intensive: 74 dB(A) re 1 pW
- Power rating: 147 W
- Light Intensity: 238 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 930-1200 x 895 x 502 mm
- Dimensions recirculating (HxWxD): 990-1260 x 895 x 502 mm
- Dimensions recirculating with CleanAir module (HxWxD):  
1120 x 895 x 502 mm - mounting with outer chimney  
1190-1460 x 895 x 502 mm - mounting with telescopic chimney
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Average Energy Consumption: 34.6 kWh/year\*

### Optional accessories

- Recirculating kit Z50XXPOX0

\* In accordance with the EU-Regulation No 65/2014

N 90, Wall-mounted cooker hood, 90 cm, clear glass black printed  
D951MT1N0B

## Dimensioned drawings

