

N 50, BUILT-UNDER FREEZER, 82 X 59.8 CM, FLAT
HINGE
G4344XFF0G



The built-in freezer with temperature rise alarm and superfreeze function.

✓ Super Freeze – Lowers the temperature temporarily to prevent frozen goods from warming up by new arrivals in the freezer

1 x ice cube tray

KU1213Z0 Attachment door, stainless steel

Energy Efficiency Class:F
Average annual energy consumption in kilowatt hour per year (kWh/a): 224 kWh/a
Sum of volume of frozen compartments: 106 l
Airborne acoustical noise emissions : 38 dB(A) re 1pW
Airborne acoustical noise emission class: C
Thermometer freeze section: Analog
Light: No
Product category: Upright freezer
Built-in / Free-standing: Built-in
Door panel options: Possible but accessory
Frost free system:No
Height of the appliance:820 mm
Width of the appliance:598 mm
Depth: 548 mm
Dimensions of the packed product (HxWxD): .890 x 670 x 620 mm
Net weight: 36.7 kg
Gross weight:39.6 kg
Connection Rating: 90 W
Fuse protection:13 A
Frequency:50 Hz
Length electrical supply cord: 230.0 cm
Door hinge:Right reversible
Defrost: manual
Warning signal / malfunction: Both visual and audible
Door lock: No
Number of drawers/baskets (Stck): 3
Number of freezing flaps (Stck):0
EAN code:4242004237693
Brand:Neff
Product name / Commercial code: G4344XFF0G
Product category: Upright freezer
Included accessories: 1 x ice cube tray



N 50, BUILT-UNDER FREEZER, 82 X 59.8 CM, FLAT
HINGE
G4344XFF0G

Functions

- Fully Integrated

Design features

- Mechanical control
- Temperature indicator on inside of door
- 1 compressor/1 cold circuit
- SuperFreeze function with automatic deactivation
- Freezer malfunction warning signal: Optic and acoustic Warning System

Key features - Freezer section

- 3 freezer drawers
- 1 ice cube tray with lid
- Right hinged door, reversible
- Ventilation through plinth
- Variable plinth adaption
- Height adjustable feet in the front
- Connection value 90 W
- 220 - 240 V

Dimension and installation

- Dimensions: 82 cm H x 59.8 cm W x 54.8 cm D
- Niche Dimensions: 82 cm H x 60 cm W x 55 cm D
- G4344XFF0G

Included accessories

- KU1213Z0

Design features

Dimension and installation

Additional features


Performance and Consumption

- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.
- EU19_EEK_D: F
- Total Volume : 106 l
- Net 4* compartment volume : 106 l
- Freezing capacity 24h : 7.4 kg
- Annual Energy Consumption: 224 kWh/a
- Climate Class: SN-T
- Noise Level : 38 dB , EU19_Noise emission class_D: C
- Temperature rise time : EU19_Temperature rise time_D: 10 H

N 50, BUILT-UNDER FREEZER, 82 X 59.8 CM, FLAT
HINGE
G4344XFF0G


measurements in mm

Recommended gap dimensions for flat hinges



F	R	X
16-19	0-3	2.5
20	0-1	3
	2-3	2.5
21	0-1	3
	2-3	2.5
22	0	4
	1	3.5
	2-3	3

The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units.



Maximal permissible weight of the unit fronts

Fitted unit fronts that exceed the permissible weight may cause damage and result in functional impairment of the hinges

Δ Weight

A: Appliance door height including hinges in mm

B: Undamped hinge, unit front in kg

C: Damped hinge, unit front in kg

D: Additional possible load in kg with heavy load kit

A	B	C	D
1500-1750	22	22	
720-1400	19	19	B+5 / C+5
A1	15	19	
A2	15	19	