


N 90, Island cooker hood, 37 cm, Black  
I38KHV2S0



The high-powered, cube-shaped hood design is a show-stopper in any kitchen

- ✓ Fully Automatic Hood – cooking is pure pleasure thanks to fully automatic hood control when the hob is switched on
- ✓ Hob-Hood Control: conveniently control the hood directly from the hob (with Wi-Fi enabled hob)
- ✓ Special noise insulation: guarantees an extremely quiet cooking experience
- ✓ EfficientDrive: save energy and enjoy a quieter kitchen thanks to efficient brushless motor technology
- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger

#### Features

##### Technical Data

Typology : Chimney  
Approval certificates : CE, VDE  
Length of electrical supply cord (cm) : 140  
Height of product, without chimney (mm) : 501  
Minimum distance above an electric hob : 550  
Minimum distance above a gas hob : 650  
Net weight (kg) : 24.530  
Type of control : Electronic  
Number of speed settings : 3-stage + 2 intensive  
Boost position output recirculating (m<sup>3</sup>/h) : 511.0  
Number of lights (Stck) : 4  
Grease filter material : Washable aluminium  
EAN code : 4242004210399  
Connection rating (W) : 272  
Current (A) : 10  
Voltage (V) : 220-240  
Frequency (Hz) : 50; 60  
Plug type : no plug  
Installation type : Island

#### Optional accessories

Z50XXP0X0 Long Life odor filter (replacement)  
Z53XXB1X6 Clean Air Plus odor filter (replacement)



# N 90, Island cooker hood, 37 cm, Black

## 138KHV2S0

### Features

#### Key performance features:

- Extraction rate in recirculation mode: Max. normal use: 392 m<sup>3</sup>/h  
Intensive: 511 m<sup>3</sup>/h

#### Features

- Climate Control Sensor
- Hob-Hood control (with Wi-Fi enabled hob)
- Touch control
- LED display
- 3 power levels and 2 intensive settings
- 4 x 3w LED Light
- Colour Temperature: 3500 K
- softLight with dimmer function
- Efficient BLDC technology
- Noise reduction function
- Interval operation
- Automatic after running (Automatic after running (10 minutes))
- Automatic intensive revert (6mins)
- Clean Air charcoal filter included
- 1 metal grease filter cassette
- Saturation indicator for metal and charcoal filter
- Additional noise insulation

#### Design

- Cable fixture for cube incl. ceiling mounting plate, easy installation  
only 4 screws, cable fixture length adjustable (20cm - 100cm)
- Electronic controls

#### Performance/technical information

- Suitable for recirculated extraction
- Max. extraction rate: 511 m<sup>3</sup>/h
- Noise levels in recirculation mode: Max. normal use: 69 dB(A) re 1 pW  
Intensive: 74 dB(A) re 1 pW
- Power rating: 272 W
- Light Intensity: 962 lux
- Electrical cable length 1.4 m
- Dimensions (HxWxD): 501 mm x 370 x 377 mm

#### Optional accessories

- Recirculating kit Z50XXPOX0

\* In accordance with the EU-Regulation No 65/2014

N 90, Island cooker hood, 37 cm, Black  
I38KHV2S0

Dimensioned drawings

