

N 70, Ceiling cooker hood, 100 cm, Stainless steel  
190CL46N0



COOKING PASSION SINCE 1877



Plug & Play ceiling hood: easy ceiling installation in recirculation mode.

- ✓ Dimmer Function – dim the LED light conveniently with the button on the remote control
- ✓ Remote Control – comfortably control the ceiling hood with a remote
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ Interval Ventilation – automatically ventilates every hour for crisp, clean air
- ✓ Automatic After-running – ventilation continues for several minutes after you turn it off

#### Features

##### Technical Data

Typology : Traditional  
Approval certificates : CE  
Length of electrical supply cord (cm) : 0  
Minimum distance above an electric hob : 600  
Minimum distance above a gas hob : 900  
Net weight (kg) : 27.636  
Type of control : Electronic  
Boost position output recirculating (m<sup>3</sup>/h) : 850.0  
Maximum output recirculating air (m<sup>3</sup>/h) : 780  
Number of lights (Stck) : 2  
Diameter of air outlet (mm) : 150  
Grease filter material : Washable aluminium  
EAN code : 4242004201717  
Connection rating (W) : 192  
Current (A) : 16  
Voltage (V) : 220-240  
Frequency (Hz) : 50  
Plug type : no plug  
Installation type : Built-in

#### Optional accessories

Z54CP00X0 Long Life odor filter (replacement)



4 242004 201717

## Features

### Features

- LED display
- 2 x 6W LED
- softLight with dimmer function
- 2 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- Stainless steel filter cover, metal grease filter
- 3 speeds plus intensive
- Interval operation
- Automatic after running (Automatic after running (30 mins))
- Automatic intensive revert (6mins)
- Rim ventilation

### Design

- Stainless steel
- Ceiling mounted hood
- Soft touch control
- Electronic controls
- Infrared remote control
- Neutral white lights

### Performance/technical information

- Suitable for recirculated extraction
- Max. extraction rate: 850 m<sup>3</sup>/h
- Extraction rate in recirculation mode:  
Max. normal use: 780 m<sup>3</sup>/h  
Intensive: 850 m<sup>3</sup>/h
- Noise levels in recirculation mode:  
Max. normal use: 70 dB(A) re 1 pW  
Intensive: 72 dB(A) re 1 pW
- Power rating: 192 W
- Light Intensity: 345 lux
- Colour Temperature: 4000 K
- Electrical cable length 0 m
- Dimensions recirculating (HxWxD): 245-245 x 1000 x 700 mm

N 70, Ceiling cooker hood, 100 cm, Stainless steel  
190CL46N0

Dimensioned drawings

