

N 90, Downdraft hood, 11 cm, clear glass black printed
191VT44NOB



COOKING PASSION SINCE 1877



A+



This domino hood offers more flexibility and a clear view while cooking thanks to its space-saving installation in the countertop.

- ✓ Maximum flexibility: Thanks to various options for combining with Domino and electric hobs.
- ✓ High extraction rate: Ensures a clear view while cooking thanks to efficient motor technology as either a ducted or recirculating solution.
- ✓ Reduced noise: Our optimised motor guarantees a quiet cooking experience.
- ✓ Space-saving installation: More room for pull-out drawers thanks to the ingenious installation of the extractor duct in a lower cabinet.
- ✓ Grease filter performance: Filters the grease right where it originates - at the hob.

Features

Technical Data

Approval certificates : CE
Length of electrical supply cord (cm) : 130
Required niche size for installation (HxWxD) : 900-1050mm x 551.0mm x 500mm
Net weight (kg) : 14.020
Type of control : Electronic
Maximum output air extraction (m³/h) : 540
Boost position output recirculating (m³/h) : 480.0
Boost position air extraction (m³/h) : 600
Noise level (dB(A) re 1 pW) : 67
Diameter of air outlet (mm) : 150
Grease filter material : Washable stainless steel
EAN code : 4242004211372
Connection rating (W) : 145
Current (A) : 16
Voltage (V) : 220-240
Frequency (Hz) : 50
Plug type : Gardy plug w/ earthing
Installation type : Built-in

Optional accessories

Z5290X0 Long Life recirculation kit external
Z52VA10X0 Gas deflector



4 242004 211372

*N 90, Downdraft hood, 11 cm, clear glass black
printed
191VT44NOB*

Features

Features

- For installation in a kitchen cabinet
- 7 segment LED display
- 1 metal grease filter cassette
- Saturation indicator for metal and charcoal filter
- Twin channel high performance fan motor
- 3 speeds plus intensive
- Automatic 10 minutes after running
- Automatic intensive revert (6mins)

Design

- Stainless steel
- Worktop ventilation
- Touch control
- Electronic controls

Performance/technical information

- Cannot be used with Domino gas hobs with Wok Burner and must not be combined with 2 standard Domino gas hobs.
- Suitable for ducted extraction and recirculation
- For recirculated extraction CleanAir recirculating kit (accessory) needed
- Efficient BLDC technology
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 540 m³/h
Intensive 600 m³/h
- Power rating: 145 W
- Noise max. Normal Level: 67 dB*
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 67 dB(A) re 1 pW (53 dB(A) re 20 µPa sound pressure)
Intensive: 70 dB(A) re 1 pW (56 dB(A) re 20 µPa sound pressure)
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 150 mm enclosed)
- Dimensions exhaust air (HxWxD): 900-1050 x 110 x 546 mm
- Dimensions recirculating (HxWxD): 900-1050 x 110 x 546 mm
- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 37.4 kWh/year*

Optional accessories

- Recirculating kit

* In accordance with the EU-Regulation No 65/2014