

N 50, ISLAND COOKER HOOD, 90 CM, CLEAR GLASS I95GBE2N0B



B

Optional accessories

Z50XXP0X0 Long Life odor filter (replacement), Z5101X1 Standard odor filter (replacement), Z5105X5 Standard recirculation kit, Z52CG1X4 Clean Air Standard recirculation kit, Z52CXC1N6 Clean Air Plus recirc. kit external, Z53CXB1X4 Clean Air Standard odor filter (repl.), Z53XXB1X6 Clean Air Plus odor filter (replacement), Z5908N1 Chimney extension 1100 mm, Z5911X0 Adapter for roof inclination left/right, Z5913X0 Adapter for roof inclination front/back, Z5918N1 Chimney extension 1600 mm, Z5920N0 Extension for mounting kit 500 mm, Z5922N0 Extension for mounting kit 1000 mm

The flat glass canopy hood accentuates the box hood design with a mix of modern materials and straight lines.

- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ LED Lighting – Clear illumination while you cook.
- ✓ Reduced Noise: our optimised motor guarantees a quiet cooking experience.
- ✓ High Extraction Rate – ensures a clear view while cooking thanks to an efficient motor technology

Features

Technical Data

Typology:	Island/Ceiling
Length electrical supply cord:	130.0 cm
Height of the chimney:	698-878/698-998 mm
Height of the appliance:	46 mm
Minimum distance above an electric hob:	550 mm
Minimum distance above a gas hob:	650 mm
Net weight:	31.8 kg
Type of control:	Electronic
Number of speed settings:	3-stages + intensive setting
Maximum output air extraction:	429 m³/h
Boost position output recirculating:	527 m³/h
Maximum output recirculating air:	390 m³/h
Boost position air extraction:	733 m³/h
Maximum Air flow:	429 m³/h
Number of lights:	4
Noise level:	60 dB(A) re 1 pW
Diameter of air outlet:	120 / 150 mm
Grease filter material:	Washable aluminium
EAN code:	4242004234968
Connection Rating:	256 W
Fuse protection:	10 A
Voltage:	220-240 V
Frequency:	50; 60 Hz
Plug type:	GB plug
Installation typology:	Island



N 50, ISLAND COOKER HOOD, 90 CM, CLEAR GLASS I95GBE2N0B

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 Ø 15 cm:
 - max. Normal use 429 m³/h
 - Intensive 733 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 60 dB dB*

- Lighting Efficiency Class: A*

- Grease Filtering Efficiency Class: B*

- Average Energy Consumption: 72.1 kWh/year*

Optional accessories

- Recirculating kit Z50XXP0X0

* In accordance with the EU-Regulation No 65/2014

Features

- Soft touch control
- 3 speeds plus intensive
- 4 x 1.5W LED Light
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- easy to clean Inner frame

Design

- Clear glass
- Island chimney hood
- Installation: Ceiling
- Electronic controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 max. 733 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 60 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 60dB(A) re 1 pW
- Intensive: 71 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 60 dB (A) re 1pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode: Max. normal use: 390m³/h
- Intensive: 527m³/h
- Noise level in recirculation mode: Max. normal use: 67dB(A) re 1 pW
- Intensive: 73 dB(A) re 1 pW
- Power rating: 256 W
- Light Intensity: 502 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Dimensions recirculating with CleanAir module (HxWxD): 812-1044 x 898 x 600 mm
- Blower Efficiency Class: B*

N 50, ISLAND COOKER HOOD, 90 CM, CLEAR GLASS
 I95GBE2N0B

Dimensioned drawings

