

N 70, ISLAND COOKER HOOD, 90 CM, STAINLESS STEEL  
I96BMP5N0B



A+



Optional accessories

Z5919N1 Chimney extension 1600 mm, Z5921N0 Extension for mounting kit 500 mm, Z5923N0 Extension for mounting kit 1000 mm, Z5912X0 Adapter for roof inclination left/right, Z5914X0 Adapter for roof inclination front/back, Z50XXP0X0 Long Life odor filter (replacement), Z5102X1 Standard odor filter (replacement), Z5106X5 Standard recirculation kit, Z52CBD2X1 Long Life recirculation kit external, Z52CBI2X4 Clean Air Standard recirculation kit, Z52CXC2N6 Clean Air Plus recirc. kit external, Z53CBB2X4 Clean Air Standard odor filter (repl.), Z53XXB1X6 Clean Air Plus odor filter (replacement), Z5909N1 Chimney extension 1100 mm

The coordinating and stylish Neff box hood is modern in design and keeps up with your cooking.

- ✓ Efficient Drive Motor – Quiet and energy-efficient hood motor for a calmer kitchen.
- ✓ Touch Control: an integrated flat surface control panel for smooth operation with a fingerswipe.
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ Dimmer Function – easily dim the light according to your mood with the touch of a button
- ✓ Interval Ventilation – automatically ventilates every hour for crisp, clean air

Features

Technical Data

Typology: .....	Island/Ceiling
Length electrical supply cord: .....	130.0 cm
Height of the chimney: .....	698-878/698-998 mm
Height of the appliance: .....	46 mm
Minimum distance above an electric hob: .....	550 mm
Minimum distance above a gas hob: .....	650 mm
Net weight: .....	28.8 kg
Type of control: .....	Electronic
Number of speed settings: .....	3-stage + 2 intensive
Maximum output air extraction: .....	445 m <sup>3</sup> /h
Boost position output recirculating: .....	457 m <sup>3</sup> /h
Maximum output recirculating air: .....	353 m <sup>3</sup> /h
Boost position air extraction: .....	867 m <sup>3</sup> /h
Maximum Air flow: .....	445 m <sup>3</sup> /h
Number of lights: .....	4
Noise level: .....	54 dB(A) re 1 pW
Diameter of air outlet: .....	120 / 150 mm
Grease filter material: .....	Washable stainless steel
EAN code: .....	4242004234982
Connection Rating: .....	166 W
Fuse protection: .....	10 A
Voltage: .....	220-240 V
Frequency: .....	50; 60 Hz
Plug type: .....	GB plug
Installation typology: .....	Island
Delay Shut off modes: .....	10 min



N 70, ISLAND COOKER HOOD, 90 CM, STAINLESS  
STEEL  
I96BMP5NOB

## Features

### Key performance features:

- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591  $\varnothing$  15 cm:
- max. Normal use 445 m<sup>3</sup>/h
- Intensive 867 m<sup>3</sup>/h
- Noise max. Normal Level: Noise, max. speed in normal us: 54 dB dB\*

### Features

- Touch control
- 3 power levels and 2 intensive settings
- 4 x 1.5w LED Light
- softLight with dimmer function
- Efficient BLDC-technology
- Interval operation
- Automatic after running (Automatic after running (10 minutes))
- Automatic intensive revert (6mins)
- 3 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- Noise reduction function
- Additional noise insulation
- easy to clean Inner frame

### Design

- Island chimney hood
- Installation: Ceiling
- Electronic controls

### Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 max. 867 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 54 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 54 dB(A) re 1 pW
- Intensive: 69 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 54 dB (A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode: Max. normal use: 353 m<sup>3</sup>/h
- Intensive: 457 m<sup>3</sup>/h
- Noise level in recirculation mode: Max. normal use: 67 dB(A) re 1 pW
- Intensive: 71 dB(A) re 1 pW
- Power rating: 166 W
- Light Intensity: 423 lux
- Colour Temperature: 3500 K

- Electrical cable length 1.3 m
- Diameter pipe  $\varnothing$  150 mm ( $\varnothing$  120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Dimensions recirculating with CleanAir module (HxWxD): 812-1044 x 898 x 600 mm
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Average Energy Consumption: 31.9 kWh/year\*

### Optional accessories

- Recirculating kit Z5919N1

\* In accordance with the EU-Regulation No 65/2014

N 70, ISLAND COOKER HOOD, 90 CM, STAINLESS  
STEEL  
I96BMP5NOB

Dimensioned drawings

