


N 90, ISLAND COOKER HOOD, 90 CM, STAINLESS
STEEL
I96BMU5N5B



A



Optional accessories

Z5923N0 Extension for mounting kit 1000 mm, Z50XXPOX0 Long Life odor filter (replacement), Z5102X1 Standard odor filter (replacement), Z5106X5 Standard recirculation kit, Z52CBD2X1 Long Life recirculation kit external, Z52CBI2X4 Clean Air Standard recirculation kit, Z52CXC2N6 Clean Air Plus recirc. kit external, Z53CBB2X4 Clean Air Standard odor filter (repl.), Z53XXB1X6 Clean Air Plus odor filter (replacement), Z5909N1 Chimney extension 1100 mm, Z5912X0 Adapter for roof inclination left/right, Z5914X0 Adapter for roof inclination front/back, Z5919N1 Chimney extension 1600 mm, Z5921N0 Extension for mounting kit 500 mm

The coordinating and stylish Neff box hood is modern in design and keeps up with your cooking.

- ✓ Fully Automatic Hood – Takes control as soon as you switch on the hob.
- ✓ Cooktop-based Hood Control – Adjust your hood's extraction level and lighting.
- ✓ Efficient Drive Motor – Quiet and energy-efficient hood motor for a calmer kitchen.
- ✓ Touch Control: an integrated flat surface control panel for smooth operation with a fingerswipe.

Features

Technical Data

Typology: Island/Ceiling
 Length electrical supply cord: 130.0 cm
 Height of the chimney: 698-878/698-998 mm
 Height of the appliance: 46 mm
 Minimum distance above an electric hob: 550 mm
 Minimum distance above a gas hob: 650 mm
 Net weight: 29.1 kg
 Type of control: Electronic
 Number of speed settings: 3-stage + 2 intensive
 Maximum output air extraction: 445 m³/h
 Boost position output recirculating: 457 m³/h
 Maximum output recirculating air: 353 m³/h
 Boost position air extraction: 867 m³/h
 Maximum Air flow: 445 m³/h
 Number of lights: 4
 Noise level: 54 dB(A) re 1 pW
 Diameter of air outlet: 120 / 150 mm
 Grease filter material: Washable stainless steel
 EAN code: 4242004234999
 Connection Rating: 172 W
 Fuse protection: 10 A
 Voltage: 220-240 V
 Frequency: 50; 60 Hz
 Plug type: GB plug
 Installation typology: Island
 Delay Shut off modes: 10 min



N 90, ISLAND COOKER HOOD, 90 CM, STAINLESS
STEEL
I96BMU5N5B

Features

Key performance features:

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 Ø 15 cm:
- max. Normal use 445 m³/h
- Intensive 867 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 54 dB dB*

Special features

- Climate Control Sensor
- Hob-Hood control (with Wi-Fi enabled hob)
- Remote Monitoring and Control for connected home appliances and operation via smartphone or tablet (only in countries where Home Connect service is available)
- The Home Connect functionality can be extended by integrating numerous applications from external cooperation partners (partnerships)
- Voice Control enabled via popular voice assistants (only in countries where this service is available)
- Adjustable color temperature (2.700 K - 5.000 K) for adaption to the room lighting available via Home Connect
- Fully automatic hood

Features

- Touch control
- 3 power levels and 2 intensive settings
- 4 x 3W LED lights
- softLight with dimmer function
- Efficient BLDC-technology
- Interval operation
- Automatic after running (Automatic after running (10 minutes))
- Automatic intensive revert (6mins)
- 3 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- Noise reduction function
- Additional noise insulation
- easy to clean Inner frame

Design

- Island chimney hood
- Installation: Ceiling
- Electronic controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 max. 867 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 54 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 54 dB(A) re 1 pW
- Intensive: 69 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 54 dB (A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional

accessory) your appliances reaches:

- Extraction rate in recirculation mode: Max. normal use: 353 m³/h
- Intensive: 457 m³/h
- Noise level in recirculation mode: Max. normal use: 67 dB(A) re 1 pW
- Intensive: 71 dB(A) re 1 pW
- Power rating: 172 W
- Light Intensity: 659 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Dimensions recirculating with CleanAir module (HxWxD): 812-1044 x 898 x 600 mm
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 36.5 kWh/year*

Optional accessories

- Recirculating kit Z5923N0

* In accordance with the EU-Regulation No 65/2014

N 90, ISLAND COOKER HOOD, 90 CM, STAINLESS
STEEL
I96BMU5N5B

Dimensioned drawings

