


N 70, Ceiling cooker hood, 90 cm, White
199C68W1GB



COOKING PASSION SINCE 1877



A



Flush with the ceiling, the stylish integrated ceiling hood leaves room for an open and clear kitchen

- ✓ Remote Control – comfortably control the ceiling hood with a remote
- ✓ LED lighting: a clear illumination whilst cooking thanks to the energy-saving LED lights
- ✓ CleanAir Recirculation Filter (separate accessory): nothing but clean air thanks to the premium recirculation filter with high odour reduction (ca. 95%). Regenerative filter also available.
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ Interval Ventilation – automatically ventilates every hour for crisp, clean air

Features

Technical Data

Typology : Traditional
 Approval certificates : CE, NEMKO
 Length of electrical supply cord (cm) : 130
 Required niche size for installation (HxWxD) : 299mm x 870.0mm x 476mm
 Minimum distance above an electric hob : 550
 Minimum distance above a gas hob : 650
 Net weight (kg) : 15.300
 Type of control : Electronic
 Maximum output air extraction (m³/h) : 583
 Boost position output recirculating (m³/h) : 570.0
 Boost position air extraction (m³/h) : 780
 Number of lights (Stck) : 4
 Noise level (dB(A) re 1 pW) : 64
 Diameter of air outlet (mm) : 150
 Grease filter material : Washable aluminium
 EAN code : 4242004219651
 Connection rating (W) : 279
 Current (A) : 10
 Voltage (V) : 220-230
 Frequency (Hz) : 50
 Plug type : GB plug
 Installation type : Built-in

Optional accessories

Z5170X1	CleanAir active carbon filter spare part
Z5190X0	CleanAir Recirculation module



4 242004 219651

N 70, Ceiling cooker hood, 90 cm, White

199C68W1GB

Features

Features

- For ceiling mounted installation
- 7 segment LED display
- 4 x LED 2.5W
- 3 metal grease filter cassettes
- metal grease filter
- Grease filter saturation indicator
- Interval operation
- 3 speeds plus intensive
- Automatic revert setting
- Rim ventilation

Design

- White
- Ceiling mounted hood
- Soft touch control
- Electronic controls
- radio remote control

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction CleanAir recirculating kit (accessory) needed
- Twin channel high performance fan motor
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 570 m³/h
Intensive 780 m³/h
- Power rating: 279 W
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 64 dB(A) re 1 pW (50 dB(A) re 20 μ Pa sound pressure)
Intensive: 71 dB(A) re 1 pW (57 dB(A) re 20 μ Pa sound pressure)
- Noise max. Normal Level: 64 dB*
- Light Intensity: 673 lux
- Colour Temperature: 4000 K
- Electrical cable length 1.3 m
- Diameter pipe \varnothing 150 mm (\varnothing 150 mm enclosed)
- Dimensions exhaust air (HxWxD): 299-299 x 900 x 500 mm
- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: E*
- Average Energy Consumption: 58.2 kWh/year*

* In accordance with the EU-Regulation No 65/2014