



Ontional accessories

Z943SE0 Set of 2 pots and 1 pan

Standalone electric hob with TouchControl

 $\sqrt{}$ Touch Control – Control your hob with just one touch and a timer.

Features

Technical Data

Product name/family: Cooking zone ceramic

Construction type : Built-in Energy input : Electric

Total number of positions that can be used at the same time : 4 Min. required niche size for installation (HxWxD) : $45 \times 560-560 \times 10^{-2}$

490-500 mm

Width of the appliance : 592 mmDimensions : $45 \times 592 \times 522 \text{ mm}$

Dimensions of the packed product (HxWxD) : $100 \times 750 \times 590$ mm

Net weight : 7.3 kg Gross weight : 8.1 kg

Frequency: 50; 60 Hz

Residual heat indicator : Separate Location of control panel : Hob front Basic surface material : Ceramic Color of surface : Black EAN code : 4242004163077 Voltage : 220-240 V





Features

Design

- Frameless
- 60 cm: space for 4 pots or pans.

Flexibility of cooking zones

- Cooking zone front left: 145 mm, 1.2 KW
- Cooking zone rear left: 180 mm, 2 KW
- Cooking zone rear right: 145 mm , 1.2 KW
- Cooking zone front right: 210 mm, 2.2 KW

Usage convenience

- Touch control: control the power with imprinted +/- touch buttons.
- Variable 17-stage power settings for each zone: precisely adapt the heat with 17 power levels (9 main levels and 8 intermediate levels).
- Timer with automatic shut off for all zones : switches off the cooking zone at the end of the time set (e.g. for boiled eggs)
- LED timer for each zone with switch off function and acoustic signal
- : an alarm sounds at the end of the time set (e.g. for pasta).

Time saving & efficiency

- ReStart function: in case of unintentional switch-off, this feature restores all previous settings by switching on the hob again within 4 seconds.
- Quick-Off: quickly switch off a cooking zone with one longer touch.


Safety


- 2 stage residual heat indicators: indicates which cooking zones are still hot or warm.
- Control panel lock: prevent unintended activation of the hob.
- Main switch: switch off all cooking zones at the touch of a button.
- Power on indicator light: indicates if the hob is heating.
- Safety cut out facility: for safety reasons, heating stops after a preset time if not used (possible to customise).

Installation

- Dimensions of the product (HxWxD mm): 45 x 592 x 522
- Required niche size for installation (HxWxD mm): 45 x 560 x (490 500)
- Min. worktop thickness: 16 mm
- Connected load: 6.6 KW







- A: Minimum distance from the hob cut-out to the wall.
 B: Recessed depth
 C: With fitted oven underneath min. 20, possibly more; see space requirements for the oven.