







### Optional accessories

Z9428FE0 Iron pan Ø 18 / 28 cm Z943SE0 Set of 2 pots and 1 pan

# Standalone electric hob with TouchControl

 $\sqrt{\ }$  Touch Control – Control your hob with a simple touch.

#### **Features**

### Technical Data

Product name/family: Cooking zone ceramic

Construction type : Built-in Energy input : Electric

Total number of positions that can be used at the same time : 4 Min. required niche size for installation (HxWxD) :  $45 \times 560-560 \times 10^{-2}$ 

490-500 mm

Width of the appliance : 592 mmDimensions :  $45 \times 592 \times 522 \text{ mm}$ 

Dimensions of the packed product (HxWxD) :  $100 \times 750 \times 590$  mm

Net weight : 7.6 kg Gross weight : 8.4 kg

Residual heat indicator : Separate Location of control panel : Hob front Basic surface material : Ceramic Color of surface : Black EAN code : 4242004163497 Voltage : 220-240 V

Voltage: 220-240 V Frequency: 50; 60 Hz





#### Feature:

### Design

- Bevelled front edge
- 60 cm: space for 4 pots or pans.

### Flexibility of cooking zones

- Ring zone double: use regular or larger cookware on the extendable cooking zone.
- Cooking zone front left: 145 mm, 1.2 KW
- Cooking zone rear left: 180 mm, 2 KW
- Cooking zone rear right: 145 mm, 1.2 KW
- Cooking zone front right: 120 mm, 210 mm, 0.75 KW

## Usage convenience

- Touch control: control the power with imprinted +/- touch buttons.
- Variable 17-stage power settings for each zone: precisely adapt the heat with 17 power levels (9 main levels and 8 intermediate levels).
- Keep warm function: Keep Warm Function: keep dishes warm at preset low power level.
- Timer with automatic shut off for all zones
  : switches off the cooking zone at the end of the time set (e.g. for boiled eggs).
- LED timer for each zone with switch off function and acoustic signal
  - : an alarm sounds at the end of the time set (e.g. for pasta).

# Time saving & efficiency

- ReStart function: in case of unintentional switch-off, this feature restores all previous settings by switching on the hob again within 4 seconds.
- Quick-Off: quickly switch off a cooking zone with one longer touch.


# Safety


- 2 stage residual heat indicators: indicates which cooking zones are still hot or warm.
- Control panel lock: prevent unintended activation of the hob.
- Control panel suspension: wipe overboiled liquids without unintentionally changing settings (blocking all touch buttons for 30 seconds)
- Main switch: switch off all cooking zones at the touch of a button.
- Power on indicator light: indicates if the hob is heating.
- Safety cut out facility: for safety reasons, heating stops after a preset time if not used (possible to customise).
- Energy consumption display: shows the electricity consumption of the last cooking process.

#### Installation

- Dimensions of the product (HxWxD mm): 45 x 592 x 522
- Required niche size for installation (HxWxD mm) :  $45 \times 560 \times (490 - 500)$
- Min. worktop thickness: 16 mm
- Connected load: 6.6 KW







- A: Minimum distance from the hob cut-out to the wall.
  B: Recessed depth
  C: With fitted oven underneath min. 20, possibly more; see space requirements for the oven.