

N 30, GAS HOB, 60 CM, BLACK  
T26BR46S0



Optional accessories

Z2480X0	Simmer plate
Z32SE10X0	Small pot support

Gas hob with side-mounted controls.

- ✓ Pan Supports - continuous cast-iron finish pan supports for maximum stability and cooking convenience.
- ✓ Sword Knobs - a better feel and easier to operate, the new knob in an attractive design.
- ✓ Coating - black enamel coating.

Features

Technical Data

Product name/family: .....	gas hob w integrated controls
Built-in / Free-standing: .....	Built-in
Energy input: .....	Gas
Number of cooking zones: .....	4
Type of control setting devices: .....	sword knobs
Min. required niche size for installation (HxWxD): ..	45 x 560-562 x 480-492 mm
Width of the appliance: .....	580 mm
Dimensions: .....	56 x 580 x 510 mm
Dimensions of the packed product (HxWxD): ..	141 x 651 x 578 mm
Net weight: .....	7.5 kg
Gross weight: .....	8.4 kg
Residual heat indicator: .....	without
Location of control panel: .....	Lateral
Basic surface material: .....	Enamel
Color of surface: .....	Black
Length electrical supply cord: .....	100.0 cm
EAN code: .....	4242004187813
Gas connection rating: .....	7400 W
Fuse protection: .....	3 A
Voltage: .....	220-240 V
Frequency: .....	60; 50 Hz



N 30, GAS HOB, 60 CM, BLACK  
T26BR46S0

## Features

### Design

- enamel surface, black
- Cast iron finish pan supports with rubber feet

### Usage convenience

- Design co-ordinated control dials: access knobs on the side with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

### Burners and power

- 4 burner hob
- Left front: High-speed burner up to 3 KW (depending on gas type)
- Left rear: Standard burner up to 1.7 KW (depending on gas type)
- Right rear: Standard burner up to 1.7 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

### Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

### Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 56 x 580 x 510
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 7.4 KW

N 30, GAS HOB, 60 CM, BLACK  
T26BR46S0

Dimensioned drawings

