


N 70, GAS HOB, 60 CM, STAINLESS STEEL
T26DS59N0



Optional accessories

| | |
|-----------|-------------------|
| Z2480X0 | Simmer plate |
| Z32SE10X0 | Small pot support |
| Z32SW10X0 | Wok ring |

The gas hob with a stainless-steel surface design and adjustable FlameSelect.

- ✓ FlameSelect® – Gain ultimate control of your flame.
- ✓ Pan Supports – continuous cast-iron pan supports for maximum stability and cooking convenience.
- ✓ Wok Burner – powerful cooking at up to 3.5 kW.
- ✓ Sword Knobs – a better feel and easier to operate, the new knob in an attractive design.
- ✓ Stainless steel surface – elegant and sophisticated design.

Features

Technical Data

Product name/family:gas hob w integrated controls
 Built-in / Free-standing: Built-in
 Energy input: Gas
 Number of cooking zones: 4
 Type of control setting devices: sword knobs
 Min. required niche size for installation (HxWxD): . 45 x 560-562 x 480-492 mm
 Width of the appliance: 582 mm
 Dimensions: 53 x 582 x 520 mm
 Dimensions of the packed product (HxWxD): . 141 x 651 x 578 mm
 Net weight: 11.4 kg
 Gross weight: 12.3 kg
 Residual heat indicator:without
 Location of control panel: Front
 Basic surface material: Stainless steel
 Color of surface:Stainless steel
 Length electrical supply cord: 100.0 cm
 EAN code:4242004203438
 Gas connection rating:8000 W
 Fuse protection:3 A
 Voltage:220-240 V
 Frequency:60; 50 Hz



N 70, GAS HOB, 60 CM, STAINLESS STEEL
T26DS59N0

Features

Design

- Stainless steel surface
- black cast iron pan supports with protective rubber feet

Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 burner hob
- Left front: Standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: WOK burner up to 3.5 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU)
Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 53 x 582 x 520
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 8 KW

N 70, GAS HOB, 60 CM, STAINLESS STEEL
T26DS59N0

Dimensioned drawings

