

N 30, BUILT-IN OVEN, 60 X 60 CM, BLACK BIDCCOAK3B







Included accessories

2 x combination grid, 1 x universal pan

Optional accessories

Z11AB15A0 Baking tray, non-stick ceramic coated, Z11AU15A0 Universal pan, non-stick ceramic coated, Z11CR10X0 Baking and roasting grid (standard), Z11GU20X0 Glasspan, Z11TI15X0 Cliprails, Z12CB10A0 Baking tray, enamelled, Z12CL10A0 Lid for professional pan, enamelled, Z12CM10A0 Moussaka pan, enamelled, Z12CN10A0 Professional pan, enamelled, Z12CP10A0 Pizza pan, enamelled, Z12CU10A0 Multipurpose pan, enamelled, Z1365WX0 Wireless food thermometer, Z13CV06S0 Decor strip, Z1608BX0 Full ext rails, level independent, Z1650BE0 Half tray, Z1655CA0 Air Fry & Grill tray, Z1913X0 Baking Stone

- $\sqrt{\mbox{ LED-Display simple, straightforward for clear reading}}$
- $\sqrt{\mbox{CircoTherm}^{\mbox{\scriptsize 0}}}$ Smart hot-air solution that lets you bake on up to three levels at once.

Features

Technical Data	
Built-in / Free-standing:	. Built-in
Integrated Cleaning system:	
Required niche size for installation (HxWxD): 585-595 x 560	0-568 x
550 mm	
Dimensions: 595x594x	548 mm
Dimensions of the packed product (HxWxD):675x660x6	690 mm
Control Panel Material:	Glass
Door Material:	Glass
Net weight:	33.7 kg
Usable volume (of cavity) - cavity 1:	71 l
Cooking method: Full width grill, Hotair gentle,	Hot Air,
Conventional heat, Hot air grilling	
Length electrical supply cord:	120 cm
EAN code:4242004	281092
Number of cavities (2010/30/EC):	1
Energy efficiency rating:	
Energy consumption per cycle conventional (2010/30/EC):	0.94
kWh/cycle	
Energy consumption per cycle forced air convection	
(2010/30/EC):	
Energy efficiency index (2010/30/EC):	81.2 %
Connection Rating:	2990 W
Fuse protection:	13 A
Voltage:22	0-240 V
Frequency:	0; 60 Hz
Plug type:	no plug
(electrical connection by electrician)	
Included accessories:2 x combination grid, 1 x unive	rsal pan





N 30, BUILT-IN OVEN, 60 X 60 CM, BLACK B1DCCOAK3B

Features

Features

- Oven with 5 main functions heating methods: CircoTherm®, Top/bottom heat, Circo-roasting, Full surface grill, CircoTherm® gentle
- \bullet Temperature range 50 °C 275 °C
- Cavity volume: 71 litre

Level independent telescopic rails

- 4 shelf positions
- Available as an accessory

Design

- Bevelled oval controls, round With Steel Trim
- Cavity inner surface: enamel anthracite

Cleaning

• Full glass inner door

Programmes/functions

- LED Display (Red)
- Electronic clock timer
- Heating up indicator
- Automatic start
- Bar handle
- Manual rapid heating up
- Interior halogen light
- Cooling fan
- Stainless-steel fan

Accessories

• 2 x combination grid, 1 x universal pan

Features

- Heat reflective glass
- Triple glazed door glazed CoolTouch door
- Control panel lock

Technical information

- 120 cm Cable length
- Nominal voltage: 220 240 V
- Total connected load electric: 2.99 KW

Performance/technical information

- Appliance dimension (hxwxd): 595 mm x 594 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Ventilation requirements please refer to the installation manual prior to fitting



N 30, BUILT-IN OVEN, 60 X 60 CM, BLACK BIDCCOAK3B

