

N 50, BUILT-IN OVEN, 60 X 60 CM, GRAPHITE-GREY B3ACE4HG0B











Included accessories

2 x combination grid, 1 x universal pan

Optional accessories

Z11AB15A0 Baking tray, non-stick ceramic coated, Z11AU15A0 Universal pan, non-stick ceramic coated, Z11CR10X0 Baking and roasting grid (standard), Z11TI15X0 Cliprails, Z12CB10A0 Baking tray, enamelled, Z12CP10A0 Pizza pan, enamelled, Z12CU10A0 Multipurpose pan, enamelled, Z1365WX0 Wireless food thermometer, Z13CR10X0 Baking and roasting grid (steam), Z13CV05S0 Cover Strip, Z1608BX0 Full ext rails, level independent, Z1655CA0 Air Fry & Grill tray, Z1913X0 Baking Stone, Z19DD10X0 Steam set for ovens

Built-in Slide&Hide $^{\tiny \odot}$ oven with fixed handle - unrestricted access to the oven interior thanks to the fully retracting oven door

- $\sqrt{\text{Slide\&Hide}^{\$}}$ The fully retracting oven door.
- $\sqrt{\mbox{CircoTherm}^{\otimes}}$ Smart hot-air solution that lets you bake on up to three levels at once.
- $\sqrt{\mbox{ Eco Clean}}$ with Easy Clean the duo that makes oven cleaning easier
- $\sqrt{\,}$ LCD-Display simple, straightforward with large characters for clear reading
- $\sqrt{\,}$ Cliprails Place dishes exactly where you want them in your oven.

Features

Technical Data
Built-in / Free-standing:
Integrated Cleaning system: EcoClean
programme, Hydrolytic
Required niche size for installation (HxWxD): 585-595 x 560-568 x
550 mm
Dimensions:
Dimensions of the packed product (HxWxD):670x660x690 mm
Control Panel Material:
Door Material:
Net weight:
Usable volume (of cavity) - cavity 1:
Cooking method: Full width grill, Hotair gentle, Hot Air,
Conventional heat, Pizza setting, Bottom heat, Hot air grilling
Length electrical supply cord:
EAN code:4242004263494
Number of cavities (2010/30/EC):
Energy efficiency rating:
Energy consumption per cycle conventional (2010/30/EC): 1.04
kWh/cycle
Energy consumption per cycle forced air convection
(2010/30/EC):
Energy efficiency index (2010/30/EC):
Connection Rating:
Fuse protection:
Voltage:
Frequency: 50; 60 Hz
Plug type:
Included accessories:2 x combination grid, 1 x universal pan
included accessories





N 50, BUILT-IN OVEN, 60 X 60 CM, GRAPHITE-GREY B3ACE4HG0R

Features

Design

- Graphite-Grey Edition
- LCD Display (White)
- Electronic clock timer
- Slide&Hide® with fixed handle
- Bar handle
- Bevelled oval controls, Retractable controls dials, oval With Steel
- · Cavity inner surface: enamel anthracite

Features

- Heat reflective glass
- Control panel lock
- Heating up indicator
- Automatic start
- Manual rapid heating up
- Interior halogen light
- Cooling fan
- Stainless-steel fan

Cleaning

- EcoCleanDirect : back panel
- EasyClean
- Full glass inner door

Programmes/functions

- Oven with 7 PC heating methods: CircoTherm®, Top/bottom heat, Circo-roasting, Full surface grill, CircoTherm® intensive, Bottom heat, CircoTherm® gentle
- Temperature range 50 °C 275 °C

Accessories

- 2 x combination grid, 1 x universal pan
- 4 shelf positions
- 1 Clip rail, Stop function

Technical information

- Cavity volume: 71 litre
- 120 cm Cable length
- Nominal voltage: 220 240 V
- Total connected load electric: 2.99 KW
- Energy efficiency rating (acc. EU Nr. 65/2014): A • Energy consumption per cycle in conventional mode: 1.04 kWh
- Energy consumption per cycle in fan-forced convection mode: 0.81
- kWh
- Number of cavities: Main cavity
- Heat source: electrical
- Cavity volume: 71 litre

Performance/technical information

- Appliance dimension (hxwxd): 595 mm x 594 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x 550 mm

- Ventilation requirements please refer to the installation manual prior to fitting
- We recommend you to choose complementary products within N50, in order to assure an optimal design combination of your Built-In appliances.




N 50, BUILT-IN OVEN, 60 X 60 CM, GRAPHITE-GREY B3ACE4HG0B

Dimensioned drawings


If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.


Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm



A: 19.5 mm

B: Space for appliance connection 320 x 115 mm







Dimensioned drawings

