N 90, Built-in oven with steam function, Stainless steel B48FT78N1B





Heating Modes NeffLight*

Optional accessories

Z11AB15A0 : Baking tray, non-stick ceramic coated , Z11GT10X3 : Glass roasting dish, 5,4I , Z11GU20X0 : Glasspan , Z11SZ00X0 : SeamlessCombination mounting kit , Z11SZ80X0 : SeamlessCombination 60 + 29cm , Z11SZ90X0 : SeamlessCombination 60 + 45cm , Z12CB10A0 : Baking tray, anthracite enamelled , Z12CM10A0 : Moussaka pan, anthracite enamelled , Z12CP10A0 : Pizza pan, anthracite enamelled , Z12CQ10A0 : Grill tray, anthracite enamelled , Z13CX62X0 : Vacuum bags 180 x 280 mm, 100 pcs. , Z13CX64X0 : Vacuum bags 240 x 350 mm, 100 pcs. , Z13TC10X0 : ComfortFlex Rail (1 level) f. steam , Z18F60X0 : Cookbook , Z1913X0 : Baking Stone , Z19DD10X0 : Steam set for ovens Built-in oven with FullSteam and SLIDE&HIDE[®] - combining all heating types and steam cooking in a single oven with unrestricted access

- $\sqrt{\rm Slide\&Hide^{\odot}}$ unrestricted access in the oven interior and easy handling due to rotating handle
- $\sqrt{\rm CircoTherm^{\odot}}$ our smart hot-air solution for simultaneous baking and roasting on up to four levels
- $\sqrt{}$ Sous-vide prepare vacuum-sealed dishes with FullSteam for a new horizon of flavour.
- $\checkmark\,$ Eco Clean with Base Clean the duo that makes oven cleaning easier
- $\sqrt{}$ FullTouch Control simple, precise oven control by fingertip touch on the smooth surface of the high resolution TFT colour display.
- $\checkmark\,$ Baking and Roasting Assistant with Automatic Programmes the duo for optimal baking at your command
- $\checkmark\,$ Multipoint Meatprobe the thermometer helps the oven regulate the temperature and automatically adjust the cooking time
- $\sqrt{}$ ComfortFlex® the telescopic rails come out far enough to let you grasp the baking sheet conveniently from the sides.
- $\checkmark\,$ LED lights Bright illumination exactly where you need it.

Features

Technical Data

Color / Material Front : Stainless steel Built-in / Free-standing : Built-in Door opening : Drop down Required niche size for installation (HxWxD) : 585-595 x 560-568 x 550 Dimensions of the product (mm) : 595 x 596 x 548 Dimensions of the packed product (HxWxD) (mm) : 670 x 650 x 690 Control Panel Material : Stainless steel Door Material : Glass Net weight (kg): 43.743 Approval certificates : CE, VDE Length electrical supply cord (cm) : 120 EAN code : 4242004214113 Current (A) : 16 Voltage (V) : 220-240 Frequency (Hz): 60; 50 Plug type : no plug Approval certificates : CE, VDE Number of cavities (2010/30/EC) : 1 Usable volume (of cavity) - NEW (2010/30/EC) : 71 Energy efficiency class (2010/30/EC) : A+ Energy consumption per cycle conventional (2010/30/EC) : 0.87 Energy consumption per cycle forced air convection (2010/30/EC) : 0.69

Energy efficiency index (2010/30/EC) : 81.2



N 90, Built-in oven with steam function, Stainless steel B48FT78N1B

Features

Design

- 5.7" TFT colour and graphics display with FullTouch control
- Cavity inner surface: Enamel anthracite

Features

- Control panel lock Automatic safety switch off Residual heat indicator Start button Door contact switch
- Temperature proposal Actual temperature display Heating up indicator Sabbath setting automatic programmes:
- MultiPoint MeatProbe
- Baking and roasting assistant, Automatic programmes
- NeffLight (2 x 20 Watt halogen lamps), LED light, On/off button
- Water tank empty indicator

Cleaning

- EcoCleanDirect : ceiling, back panel, side liners
- EcoClean programme, Base Clean programme
- Programmes/functions
- Additional functions: De-scaling programme Drying function Automatic boiling point detection
- Number of automatic programmes: 30 PC
- Rapid heat
- Cooling fan

Accessories

- 1-level flexible telescopic rail, full extension, Stop function
- 2 x grid, 1 x sponge, 1 x steam container, punched, size S, 1 x steam container, punched, size XL, 1 x steam container, unpunched, size S, 1 x universal pan

Performance/technical information

- Energy efficiency rating (acc. EU Nr. 65/2014): A+ Energy consumption per cycle in conventional mode: 0.87 kWh Energy consumption per cycle in fan-forced convection mode: 0.69 kWh Number of cavities: Main cavity Heat source: electrical Cavity volume: 71 litre
- 1 | Water tank capacity
- Location of water tank: Outside cavity
- Total connected load electric: 3.45 KW
- Temperature range 40 °C 250 °C
- 120 cm Cable length
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 595 mm x 596 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual