

# N 90, BUILT-IN OVEN WITH ADDED STEAM FUNCTION, 60 X 60 CM, STAINLESS STEEL B57VS26N0B













# Included accessories

2 x combination grid, 1 x universal pan

# Optional accessories

Z11AB15A0 Baking tray, non-stick ceramic coated, Z11AU15A0 Universal pan, non-stick ceramic coated, Z11CG10X0 Barbecue-Set, Z11CR10X0 Baking and roasting grid (standard), Z11GT10X3 Glass roasting dish, 5,4l, Z11GU20X0 Glasspan, Z11SZ00X0 SeamlessCombination mounting kit, Z11SZ80X0 SeamlessCombination 60 + 29cm, Z11SZ90X0 SeamlessCombination 60 + 45cm, Z11TC10X0 ComfortFlex Rail (1 level), Z11TC16X0 ComfortFlex Rail (1 level) and racks, Z12CB10A0 Baking tray, enamelled, Z12CL10A0 Lid for professional pan, enamelled, Z12CM10A0 Moussaka pan, enamelled, Z12CN10A0 Professional pan, enamelled, Z12CP10A0 Pizza pan, enamelled, Z12CQ10A0 Grill tray, enamelled, Z12CU10A0 Multipurpose pan, enamelled, Z12TF16X0 1 level telescopic rails, full ext,pyro, Z12TF36X0 3 level telescopic rails, full ext,pyro, Z13CR10X0 Baking and roasting grid (steam), Z13CV05S0 Cover Strip, Z1913X0 Baking Stone, Z19DD10X0 Steam set for ovens

# Built-in oven with VarioSteam® and SLIDE&HIDE® - fuller flavour and unrestricted access to the oven interior

- $\sqrt{\mbox{Slide\&Hide@}}$  The fully disappearing oven door with rotating handle.
- $\sqrt{\text{CircoTherm}^{\circledcirc}}$  Smart hot-air solution that lets you bake on up to four levels.
- $\sqrt{\mbox{ Vario Steam}}$  Cooks food moist on the inside and crisp on the outside.
- $\sqrt{}$  Dual cleaning options: Pyrolytic cleaning programmes just let the oven interior clean itself. EasyClean the quick and easy option for day to day maintenance.
- $\sqrt{\ }$  Shift Control fast navigation through menus and simple operation with the TFT display.

# Features

Technical Data Built-in / Free-standing:	
Integrated Cleaning system:	
Dimensions:	
Dimensions of the packed product (HxWxD): . 675 x 660 x 690 mm	
Control Panel Material: Glass	
Door Material:	
Net weight:	
Usable volume (of cavity) - cavity 1:	
Cooking method: Regeneration,	
CircoTherm®, Defrost, Bread Baking Setting, Full width grill, Hot	
Air-Eco, Half width grill, Conventional heat, Conventional heat	
ECO, Pizza setting, low temperature cooking, Bottom heat, Hot air	
grilling, warming	
Oven control: electronic	
Length electrical supply cord:	
EAN code:	
Energy efficiency rating:	
Energy consumption per cycle conventional (2010/30/EC): 0.87	
kWh/cycle	
Energy consumption per cycle forced air convection	
(2010/30/EC):	
Energy efficiency index (2010/30/EC):	
Connection Rating:	
Fuse protection:	
Voltage:	
Frequency:	
Plug type: no plug	
Plug type: no plug (electrical connection by electrician)	
Plug type: no plug	





# N 90, BUILT-IN OVEN WITH ADDED STEAM FUNCTION, 60 X 60 CM, STAINLESS STEEL B57VS26N0B

# Features

- 4.1" TFT colour and graphics display with ShiftControl
- Water tank empty indicator
- LED light, On/off button
- Slide&Hide® with fixed handle, SoftOpen
- MultiPoint MeatProbe

### Features

- Additional heating methods with steam: Reheat with steam, Dough proving
- Door lock during pyrolytic cleaning
- Control panel lock Automatic safety switch off Residual heat indicator Start button Door contact switch
- Electronic clock timer
- Additional functions:
- De-scaling programme
- Drying function steam cooking function
- Number of automatic programmes: 14 PC
- Baking and roasting assistant, Automatic programmes
- Rapid heat
- Cooling fan
- Stainless-steel fan

## Design

• Cavity inner surface: enamel anthracite

# Cleaning


- Pyrolytic cleaning
- EasyClean
- 1 x universal pan, 2 x combination grid


# Technical information


- Cavity volume: 71 litre
- Location of water tank: Outside cavity
- 120 cm Cable length
- Total connected load electric: 3.45 KW
- Appliance dimension (hxwxd): 595 mm x 596 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual



# N 90, BUILT-IN OVEN WITH ADDED STEAM FUNCTION, 60 X 60 CM, STAINLESS STEEL B57VS26N0B







If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm