

N 50, built-in oven, 60 x 60 cm, Stainless steel
B6ACH7HNOB



COOKING PASSION SINCE 1877



- ✓ Slide&Hide® with fixed handle - the fully retracting oven door.
- ✓ LCD-Display – simple, straightforward with large characters for clear reading
- ✓ Clip-on Rail - easily removed and installed telescopic rails for flexible use on all shelf levels

Features

Technical Data

Color / Material Front : Stainless steel
Built-in / Free-standing : Built-in
Integrated Cleaning system : Hydrolytic, Hydrolytic, Pyrolytic
Required niche size for installation (HxWxD) : 585-595 x 560-568 x 550
Dimensions : 595 x 594 x 548
Dimensions of the packed product (HxWxD) (mm) : 670 x 700 x 660
Control Panel Material : Glass
Door Material : Glass
Net weight (kg) : 39.824
Usable volume (of cavity) - cavity 1 (l) : 71
Cooking method : Bottom heat, Bread Baking Setting, Conventional heat, Full width grill, Hot Air, Hotair gentle, Hot air grilling, Pizza setting
First cavity material : Other
Temperature control : electronic
Number of interior lights : 1
Approval certificates : CE, VDE
Length electrical supply cord (cm) : 120
EAN code : 4242004225256
Number of cavities (2010/30/EC) : 1
Energy efficiency rating : A
Energy consumption per cycle conventional (2010/30/EC) : 1.04
Energy consumption per cycle forced air convection (2010/30/EC) : 0.81
Energy efficiency index (2010/30/EC) : 95.3
Connection Rating (W) : 2990
Current (A) : 13
Voltage (V) : 220-240
Frequency (Hz) : 60; 50
Plug type : no plug

Optional accessories

- Z11AB15A0 Baking tray, non-stick ceramic coated
- Z11CB10E0 Baking tray, grey enamelled
- Z11CR10X0 Baking and roasting grid (standard)
- Z11GT10X3 Glass roasting dish, 5,4l
- Z11TF36X0 3 level telescopic rails, full ext
- Z11TI15X0 Cliprails
- Z1913X0 Baking Stone
- Z19DD10X0 Steam set for ovens



4 242004 225256

N 50, built-in oven, 60 x 60 cm, Stainless steel
B6ACH7HNOB



COOKING PASSION SINCE 1877

Features

Design

- LCD-Display Control (white)
- Cavity inner surface: enamel grey
- Slide&Hide® with fixed handle

Features

- Door lock during pyrolytic cleaning
Control panel lock
Automatic safety switch off
Residual heat indicator
- Temperature proposal
Actual temperature display
Heating up indicator
Automatic start
- Interior halogen light

Cleaning

- Pyrolytic cleaning
- EasyClean

Programmes/functions

- Rapid heat
- Cooling fan

Accessories

- 1 Clip rail, Stop function
- 1 x universal pan, 2 x combination grid

Performance/technical information

- Energy efficiency rating (acc. EU Nr. 65/2014): A
Energy consumption per cycle in conventional mode: 1.04 kWh
Energy consumption per cycle in fan-forced convection mode:
0.81 kWh
Number of cavities: Main cavity
Heat source: electrical
Cavity volume: 71 litre
- Total connected load electric: 2.99 KW
- 120 cm Cable length
- Nominal voltage: 220 - 240 V
- Appliance dimension (hxwxh): 595 mm x 594 mm x 548 mm
- Niche dimension (hxwxh): 585 mm - 595 mm x 560 mm - 568 mm
x 550 mm
- Please refer to the dimensions provided in the installation manual

