

*N 30, TELESCOPIC COOKER HOOD, 60 CM, SILVER
METALLIC
D46BR22N1B*



Optional accessories

Z51ITB1X4	Clean Air Standard odor filter (repl.)
Z51ITI1X4	Clean Air Standard recirculation kit
Z54TS01X0	Standard recirculation kit

Telescopic hood: designed to provide powerful extraction without impacting on your kitchen space or design. These hoods pull out from underneath a cabinet when required for a streamlined kitchen.

- ✓ LED Lighting – Clear illumination while you cook.
- ✓ Integrated Power Button – the telescopic hood automatically starts and stops when you slide it out and back in

Features

Technical Data

Typology:	Pull-out
Length electrical supply cord:	175 cm
Required niche size for installation (HxWxD):	162mm x 526.0mm x 290mm mm
Height of the appliance:	203 mm
Minimum distance above an electric hob:	430 mm
Minimum distance above a gas hob:	650 mm
Net weight:	8.4 kg
Type of control:	mechanical
Number of speed settings:	3
Maximum output air extraction:	388 m³/h
Maximum output recirculating air:	257 m³/h
Maximum Air flow:	388 m³/h
Number of lights:	2
Noise level:	67 dB(A) re 1pW
Diameter of air outlet:	120 / 150 mm
Grease filter material:	Washable aluminium
EAN code:	4242004250784
Connection Rating:	108 W
Fuse protection:	10 A
Voltage:	220-240 V
Frequency:	50 Hz
Plug type:	GB plug
Installation typology:	Built-in



N 30, TELESCOPIC COOKER HOOD, 60 CM, SILVER
METALLIC
D46BR22N1B

Features

Features

- 3 power levels
- Automatic On/Off operation when telescopic canopy is pulled out and pushed back
- 2 x 1,5W LED
- Capacitor motor
- 2 metal grease filter cassettes

Design

- 60 cm wide
- Silver metallic grey
- Handle strip specification: stainless steel with logo
- Filter cover stainless steel, perforated and dishwasher safe

Performance

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit (accessory) needed
- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 389 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 67 dB(A) re 1 pW
- Colour Temperature: 3500 K
- Light Intensity: 131 lux
- Power rating: 108 W
- Average Energy Consumption: 40.3 kWh/year*
- Blower Efficiency Class: C*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*





Planning and installation information

- Installation Installation: Cupboard 60 cm
- Dimensions (HxWxD): 203 x 598 x 290 mm
- Built-in dimensions (HxWxD): 162 x 526 x 290 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Electrical cable length 1.75 m

* In accordance with the EU-Regulation No 65/2014

N 30, TELESCOPIC COOKER HOOD, 60 CM, SILVER
METALLIC
D46BR22N1B

Dimensioned drawings



Dimensioned drawings

