

N 30, canopy cooker hood, 53 cm, Silver metallic
D5655X0GB



COOKING PASSION SINCE 1877



Features

Technical Data

Typology : Traditional
Approval certificates : CE, VDE
Length electrical supply cord (cm) : 130
Required niche size for installation (HxWxD) : 255mm x 500mm x 350mm
Minimum distance above an electric hob : 650
Minimum distance above a gas hob : 650
Net weight (kg) : 7.439
Type of control : mechanical
Maximum output air extraction (m³/h) : 420
Boost position output recirculating (m³/h) : 430
Maximum output recirculating air (m³/h) : 320
Boost position air extraction (m³/h) : 650
Number of lights : 2
Noise level (dB(A) re 1 pW) : 59
Diameter of air outlet (mm) : 150 / 120
Grease filter material : Washable aluminium
EAN code : 4242004176527
Connection Rating (W) : 240
Current (A) : 10
Voltage (V) : 220-240
Frequency (Hz) : 50
Plug type : GB plug
Installation typology : Built-in



4 242004 176527

Optional accessories

Z5155X0 Accessories extractor hoods

N 30, canopy cooker hood, 53 cm, Silver metallic
D5655X0GB

Features

Features

- 2 x 20W low energy halogen lamps
- 2 metal grease filter cassettes
- 3 speeds plus intensive

Design

- Silver metallic grey
- Canopy hood
- Slide control operation
- Mechanical controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction charcoal filter (accessory) needed
- Twin channel high performance fan motor
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 420 m³/h
Intensive 650 m³/h
-
- Noise level according to EN 60704-3 and EN 60704-2-13 at
maximum normal setting: extraction rate: 59 dB (A) re 1pW
- Noise max. Normal Level: 59 dB*
- Light Intensity: 335 lux
- Colour Temperature: 2800 K
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 255-255 x 530 x 380 mm
- Dimensions recirculating (HxWxD): 255-255 x 530 x 380 mm
- Energy Efficiency Class: D (at a range of energy efficiency classes
from A+++ to D)
- Blower Efficiency Class: D*
- Lighting Efficiency Class: F*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 111.4 kWh/year*

Optional accessories

- Recirculating kit

* In accordance with the EU-Regulation No 65/2014