

*N 30, WALL-MOUNTED COOKER HOOD, 60 CM,
CLEAR GLASS, STAINLESS STEEL
D64GBC0N0B*



The flat glass canopy hood accentuates the box hood design with a mix of modern materials and straight lines.

- ✓ LED Lighting – Clear illumination while you cook.
- ✓ High Extraction Rate – ensures a clear view while cooking thanks to an efficient motor technology

Z50XXP0X0	Long Life odor filter (replacement)
Z51DXB1X4	Clean Air Standard odor filter (repl.)
Z51DXI1X4	Clean Air Standard recirculation kit
Z51DXI1X6	Clean Air Plus recirculation kit
Z51FXC1N6	Clean Air Plus recirc. kit external
Z51FXD1N1	Long Life recirculation kit external
Z51FXJ0X0	Long Life recirculation kit
Z53XXB1X6	Clean Air Plus odor filter (replacement)
Z5860N0	Back panel stainless steel
Z5865N0	Stainless steel back panel 600 mm
Z5905N0	Chimney extension 1000 mm
Z5915N0	Chimney extension 1500 mm

Typology:Wall-mounted
 Length electrical supply cord:130.0 cm
 Height of the chimney:576-906/576-998 mm
 Height of the appliance:59 mm
 Minimum distance above an electric hob:550 mm
 Minimum distance above a gas hob:650 mm
 Net weight:14.0 kg
 Type of control:mechanical
 Number of speed settings:3
 Maximum output air extraction:650 m³/h
 Maximum output recirculating air:422 m³/h
 Maximum Air flow:650 m³/h
 Number of lights:2
 Noise level:70 dB(A) re 1pW
 Diameter of air outlet:120 / 150 mm
 Grease filter material:Washable aluminium
 EAN code:4242004224051
 Connection Rating:220 W
 Fuse protection:10 A
 Voltage:220-240 V
 Frequency:50; 60 Hz
 Plug type:GB plug
 Installation typology:Wall-mounted



*N 30, WALL-MOUNTED COOKER HOOD, 60 CM,
CLEAR GLASS, STAINLESS STEEL
D64GBCON0B*

Key performance features:

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Max. extraction rate: 649 m³/h
- Noise max. Normal Level: 70 dB*

Features

- Push button control operation
- 3 power levels
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- 1 metal grease filter cassette
- For wall mounted installation

Design

- Chimney hood
- Mechanical controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Maximum extraction rate exhaust air 649 m³/h according to EN 61591
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 70 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode: Max. normal use: 422 m³/h
- Noise level in recirculation mode: Max. normal use: 74 dB(A) re 1 pW
- Power rating: 220 W
- Light Intensity: 110 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 635-965 x 600 x 525 mm
- Dimensions recirculating (HxWxD): 635-1075 x 600 x 525 mm
- Dimensions recirculating with CleanAir module (HxWxD):
- 703 x 600 x 525 mm - mounting with outer chimney
- 833-1163 x 600 x 525 mm - mounting with telescopic chimney
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 42.4 kWh/year*

Optional accessories

- Recirculating kit Z50XXP0X0

* In accordance with the EU-Regulation No 65/2014

N 30, WALL-MOUNTED COOKER HOOD, 60 CM,
CLEAR GLASS, STAINLESS STEEL
D64GBC0N0B

