

N 90, wall-mounted cooker hood, 90 cm, Stainless steel
D79MT86N1B



COOKING PASSION SINCE 1877



A



Features

Technical Data

Typology : Chimney
Approval certificates : CE, VDE
Length electrical supply cord (cm) : 130
Height of the chimney (mm) : 582-908/582-1018
Height of product, without chimney (mm) : 46
Minimum distance above an electric hob : 550
Minimum distance above a gas hob : 650
Net weight (kg) : 20.613
Type of control : Electronic
Number of speed settings : 3-stage + 2 intensive
Maximum output air extraction (m³/h) : 600
Boost position output recirculating (m³/h) : 480.0
Boost position air extraction (m³/h) : 790
Number of lights : 3
Noise level (dB(A) re 1 pW) : 66
Diameter of air outlet (mm) : 150 / 120
Grease filter material : Washable stainless steel
EAN code : 4242004183679
Connection Rating (W) : 269
Current (A) : 10
Voltage (V) : 220-240
Frequency (Hz) : 60; 50
Plug type : GB plug
Installation typology : Wall-mounted



4 242004 183679

Optional accessories

Z50XP0X0	Long Life odor filter (replacement)
Z5102X5	Standard recirculation kit
Z5170X1	CleanAir active carbon filter spare part
Z5276X0	CleanAir Recirculation Kit
Z5895N0	Stainless steel back panel
Z5906N1	Chimney extension 1000 mm
Z5916N1	Chimney extension 1500 mm

N 90, wall-mounted cooker hood, 90 cm, Stainless steel
D79MT86N1B

Features

Features

- For wall mounted installation
- 7 segment LED display
- 3 x LED lights
- softLight with dimmer function
- 3 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- Stainless steel filter cover, metal grease filter
- Interval operation
- 3 power levels and 2 intensive settings
- Automatic after running (10 minutes)
- Automatic intensive revert (6mins)
- Additional noise insulation
- 1000EE
- Rim ventilation

Design

- Stainless steel
- Stainless steel
- Chimney hood
- Box slimline brand design
- Touch control
- Electronic controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Twin channel high performance fan motor
- In recirculation operation chimless use possible
- Easy mounting system
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 600 m³/h
Intensive 790 m³/h
-
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 66 dB (A) re 1pW
- Noise max. Normal Level: 66 dB*
- Light Intensity: 897 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 628-954 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 628-1064 x 900 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD):
689 x 900 x 500 mm - mounting with outer chimney
809-1139 x 900 x 500 mm - mounting with telescopic chimney
- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 33.3 kWh/year*

Optional accessories

- Recirculating kit Z5102X1, Z5102X5, Z5276X0, Z5906N1, Z5916N1

* In accordance with the EU-Regulation No 65/2014