

N 70, WALL-MOUNTED COOKER HOOD, 60 CM,
STAINLESS STEEL
D86DK62N0B



B

- ✓ 7 segment LED display
- ✓ Interval operation
- ✓ 2 x 20W low energy halogen lamps
- ✓ 2 metal grease filter cassettes
- ✓ SoftLight with dimmer function

Z50XXPOX0	Long Life odor filter (replacement)
Z5101X1	Standard odor filter (replacement)
Z5101X5	Standard recirculation kit
Z5170X1	CleanAir active carbon filter spare part
Z5270X0	CleanAir Recirculation Kit
Z5905N0	Chimney extension 1000 mm
Z5915N0	Chimney extension 1500 mm

Typology:	Wall-mounted
Length electrical supply cord:	130.0 cm
Height of the chimney:	582-911/582-1021 mm
Height of the appliance:	59 mm
Minimum distance above an electric hob:	550 mm
Minimum distance above a gas hob:	650 mm
Net weight:	15.0 kg
Type of control:	Electronic
Number of speed settings:	3-stage + 2 intensive
Maximum output air extraction:	450 m³/h
Boost position output recirculating:	380.0 m³/h
Maximum output recirculating air:	310 m³/h
Boost position air extraction:	790 m³/h
Maximum Air flow:	450 m³/h
Number of lights:	2
Noise level:	59 dB(A) re 1pW
Diameter of air outlet:	120 / 150 mm
Grease filter material:	Washable aluminium
EAN code:	4242004175049
Connection Rating:	200 W
Fuse protection:	10 A
Voltage:	220-240 V
Frequency:	50; 60 Hz
Plug type:	GB plug
Installation typology:	Wall-mounted
Delay Shut off modes:	10 min



N 70, WALL-MOUNTED COOKER HOOD, 60 CM,
STAINLESS STEEL
D86DK62NOB

Special features

- 7 segment LED display
- Interval operation

Features

- 2 x 20W low energy halogen lamps
- 2 metal grease filter cassettes
- SoftLight with dimmer function

Design

- 60 cm wide
- For wall mounted installation
- Soft touch control for extractor speeds and light
- Height adjustable

Performance/technical information

- Suitable for ducted extraction and recirculation
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 450 m³/h
 - Intensive 790 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 59 dB (A) re 1pW (45 dB (A) re 20 µPa sound pressure)
- 3 power levels and 2 intensive settings
- Automatic revert setting
- Installation system: Chimney hood wall fixing syst.

Optional accessories

- Recirculating kit Z50XXPOX0

