

N 30, WALL-MOUNTED COOKER HOOD, 90 CM,
CLEAR GLASS
D89GR22N0B



- ✓ 2 x 40 Watt lamps
- ✓ 1 metal grease filter cassette
- ✓ 90 cm wide
- ✓ For wall mounted installation
- ✓ Glass canopy

Z50XXP0X0	Long Life odor filter (replacement)
Z5101X1	Standard odor filter (replacement)
Z5101X5	Standard recirculation kit
Z5170X1	CleanAir active carbon filter spare part
Z5270X0	CleanAir Recirculation Kit
Z5905N0	Chimney extension 1000 mm
Z5915N0	Chimney extension 1500 mm

Typology:Wall-mounted
 Length electrical supply cord: 130.0 cm
 Height of the chimney:581-897/581-1007 mm
 Height of the appliance: 57 mm
 Minimum distance above an electric hob:550 mm
 Minimum distance above a gas hob:650 mm
 Net weight: 24.6 kg
 Type of control: mechanical
 Number of speed settings: 3
 Maximum output air extraction:450 m³/h
 Maximum output recirculating air: 290 m³/h
 Maximum Air flow: 450 m³/h
 Number of lights: 2
 Noise level: 62 dB(A) re 1pW
 Diameter of air outlet:120 / 150 mm
 Grease filter material: Washable aluminium
 EAN code:4242004176213
 Connection Rating: 170 W
 Fuse protection: 10 A
 Voltage: 220-240 V
 Frequency: 50; 60 Hz
 Plug type: GB plug
 Installation typology:Wall-mounted



N 30, WALL-MOUNTED COOKER HOOD, 90 CM,
CLEAR GLASS
D89GR22NOB

Features

- 2 x 40 Watt lamps
- 1 metal grease filter cassette

Design

- 90 cm wide
- For wall mounted installation
- Glass canopy
- Clear glass
- Switch control operation for extractor speeds and light

Performance/technical information

- Suitable for ducted extraction and recirculation
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 62 dB (A) re 1pW (48 dB (A) re 20 µPa sound pressure)
- 3 power levels
- Installation system: Chimney hood wall fixing syst.

Optional accessories

- Recirculating kit Z50XXP0X0

