

N 50, WALL-MOUNTED COOKER HOOD, 90 CM,  
CLEAR GLASS  
D94AFM1NOB



**B**

**Optional accessories**

Z50XXPOX0 Long Life odor filter (replacement), Z51DXA0X0 Standard odor filter (replacement), Z51DXB1X4 Clean Air Standard odor filter (repl.), Z51DXI1X4 Clean Air Standard recirculation kit, Z51DXI1X6 Clean Air Plus recirculation kit, Z51DXU0X0 Standard recirculation kit, Z51FXC1N6 Clean Air Plus recirc. kit external, Z51FXD1N1 Long Life recirculation kit external, Z51FXJ0X0 Long Life recirculation kit, Z53XXB1X6 Clean Air Plus odor filter (replacement), Z5861N0 Back panel stainless steel, Z5895N0 Stainless steel back panel 900 mm, Z5905N0 Chimney extension 1000 mm, Z5915N0 Chimney extension 1500 mm

The curved glass canopy hood combines two design styles: transparent glass as well as the classic box hood design.

- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ LED Lighting – Clear illumination while you cook.
- ✓ Reduced Noise: the low-noise motor makes it possible to listen to your own kitchen story
- ✓ High Extraction Rate – ensures a clear view while cooking thanks to an efficient motor technology

**Features**

**Technical Data**

Typology: .....Wall-mounted  
 Length electrical supply cord: ..... 130.0 cm  
 Height of the chimney: .....576-897/576-1007 mm  
 Height of the appliance: ..... 50 mm  
 Minimum distance above an electric hob: ..... 550 mm  
 Minimum distance above a gas hob: ..... 650 mm  
 Net weight: ..... 15.8 kg  
 Type of control: ..... Electronic  
 Number of speed settings: .....3-stages + intensive setting  
 Maximum output air extraction: .....371 m<sup>3</sup>/h  
 Boost position output recirculating: .....441 m<sup>3</sup>/h  
 Maximum output recirculating air: ..... 337 m<sup>3</sup>/h  
 Boost position air extraction: .....610 m<sup>3</sup>/h  
 Maximum Air flow: ..... 371 m<sup>3</sup>/h  
 Number of lights: ..... 2  
 Noise level: ..... 61 dB(A) re 1 pW  
 Diameter of air outlet: .....120 / 150 mm  
 Grease filter material: ..... Washable aluminium  
 EAN code: .....4242004224150  
 Connection Rating: ..... 220 W  
 Fuse protection: .....10 A  
 Voltage: ..... 220-240 V  
 Frequency: .....50; 60 Hz  
 Plug type: ..... GB plug  
 Installation typology: .....Wall-mounted



N 50, WALL-MOUNTED COOKER HOOD, 90 CM,  
CLEAR GLASS  
D94AFMINOB

Features

**Key performance features:**

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 371 m<sup>3</sup>/h
- Intensive 610 m<sup>3</sup>/h
- Noise max. Normal Level: 61 dB\*

**Features**

- Touch control
- LED display
- 3 speeds plus intensive
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 1 metal grease filter cassette
- For wall mounted installation

**Design**

- Chimney hood
- Electronic controls

**Performance/technical information**

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Max. extraction rate: 610 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 61 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 61 dB(A) re 1 pW
- Intensive: 69 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 61 dB (A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode: Max. normal use: 337 m<sup>3</sup>/h
- Intensive: 441 m<sup>3</sup>/h
- Noise level in recirculation mode: Max. normal use: 70 dB(A) re 1 pW
- Intensive: 74 dB(A) re 1 pW
- Power rating: 220 W
- Light Intensity: 232 lux
- Electrical cable length 1.3 m
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 617-947 x 900 x 488 mm
- Dimensions recirculating (HxWxD): 617-1057 x 900 x 488 mm
- Dimensions recirculating with CleanAir module (HxWxD):
- 686 x 900 x 488 mm - mounting with outer chimney
- 815-1145 x 900 x 488 mm - mounting with telescopic chimney
- Blower Efficiency Class: B\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Average Energy Consumption: 47.2 kWh/year\*

**Optional accessories**

- Recirculating kit Z50XXP0X0

\* In accordance with the EU-Regulation No 65/2014

N 50, WALL-MOUNTED COOKER HOOD, 90 CM,  
CLEAR GLASS  
D94AFM1NOB

Dimensioned drawings

