

# N 70, WALL-MOUNTED COOKER HOOD, 90 CM, CLEAR GLASS BLACK PRINTED D95FRM1S0B





# Optional accessories

Z50XXP0X0	Long Life odor filter (replacement)
Z51AFB1X6	Clean Air Plus odor filter (replacement)
Z51AFI1X6	Clean Air Plus recirculation kit
Z51AFR0X0	Long Life recirculation kit (chimless)
Z51AFS0X0	Long Life recirculation kit
Z51AFV1X6	Clean Air Plus recirc. kit (chimless)
Z51AXC1N6	Clean Air Plus recirc. kit external
Z51AXK0N0	Chimney extension 1000 mm
Z51AXL0N0	Chimney extension 1500 mm
Z53XXB1X6	Clean Air Plus odor filter (replacement)
Z91AXE1S1	Chimney standard black

The Creative Slimline hood does not only offer high-performance but is also magnetic, can be written on and can be used as a bookshelf

- $\sqrt{}$  Efficient Drive Motor Quiet and energy-efficient hood motor for a calmer kitchen.
- $\sqrt{\,}$  TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- $\sqrt{\,}$  Intensive speed setting: increases the extraction rate when the steam gets intense
- $\sqrt{\mbox{ LED Lighting}}$  Clear illumination while you cook.

# Features

Technical Data	
Typology:	Wall-mounted
Length electrical supply cord:	130.0 cm
Height of the appliance:	430 mm
Minimum distance above an electric hob:	450 mm
Net weight:	22.7 kg
Type of control:	Electronic
Number of speed settings:3-st	ages + intensive setting
Maximum output air extraction:	405 m <sup>3</sup> /h
Boost position output recirculating:	404 m <sup>3</sup> /h
Maximum output recirculating air:	249 m³/h
Boost position air extraction:	739 m <sup>3</sup> /h
Maximum Air flow:	405 m³/h
Number of lights:	2
Noise level:	58 dB(A) re 1 pW
Diameter of air outlet:	120 / 150 mm
Grease filter material:	Washable
aluminium	
EAN code:	4242004210177
Connection Rating:	143 W
Fuse protection:	10 A
Voltage:	220-240 V
Frequency:	60; 50 Hz
Plug type:	
Installation typology:	Wall-mounted





# N 70, WALL-MOUNTED COOKER HOOD, 90 CM, CLEAR GLASS BLACK PRINTED D95FRM1S0B

## Features

### Key performance features:

- $\bullet$  Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use404m3/h
- Intensive739 m³/h
- Noise max. Normal Level: 58 dB\*

#### Features

- Touch control
- LED display
- 3 speeds plus intensive
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- easy to clean Inner frame
- For wall mounted installation
- Rim ventilation

### Design

- Chimney hood
- Electronic controls

# Performance/technical information

- Installation with gas hob not recommended
- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Installation system: Wall fixing inclined/flat/cube
- Extraction rate according to EN 61591 max. 404 m<sup>3</sup>/h
- • Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 58 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use:58dB(A) re 1 pW
- Intensive:71 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1pW
- Power rating: 143 W
- Light Intensity: 225 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 981-1251 x 890 x 362 mm
- Dimensions recirculating (HxWxD): 1041-1311 x 890 x 362 mm
- Dimensions recirculating with CleanAir module (HxWxD):
- $1171 \times 890 \times 362$ mm mounting with outer chimney
- 1241-1511  $\times$  890  $\times$  362 mm mounting with telescopic chimney
- Blower Efficiency Class: B\*
- Lighting Efficiency Class: A\*
- $\bullet$  Grease Filtering Efficiency Class:  $\mathsf{B}^{\textstyle\star}$
- Average Energy Consumption: 39 kWh/year\*

## Optional accessories

• Recirculating kit Z50XXP0X0

\* In accordance with the EU-Regulation No 65/2014



# N 70, WALL-MOUNTED COOKER HOOD, 90 CM, CLEAR GLASS BLACK PRINTED D95FRM1S0B

