


N 90, wall-mounted cooker hood, 90 cm, clear glass black printed
D951MT1N0B



COOKING PASSION SINCE 1877



The design hood with an inclined front and high power ensures headroom while cooking.

- ✓ Oven fit: bring harmony to your kitchen
- ✓ Ambient Light – Individualized lighting with endless colour shades via Home Connect.
- ✓ Efficient Drive Motor – Quiet and energy-efficient hood motor for a calmer kitchen.
- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense

Features

Technical Data

Typology : Wall-mounted
 Approval certificates : CE, VDE
 Length electrical supply cord : 130 cm
 Height of product, without chimney : 323 mm
 Minimum distance above an electric hob : 450 mm
 Minimum distance above a gas hob : 650 mm
 Net weight : 22.7 kg
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction : 431 m³/h
 Boost position output recirculating : 632.0 m³/h
 Maximum output recirculating air : 410 m³/h
 Boost position air extraction : 714 m³/h
 Number of lights : 2
 Noise level : 53 dB(A) re 1 pW
 Diameter of air outlet : 150 / 120 mm
 Grease filter material : Washable aluminium
 EAN code : 4242004230786
 Connection Rating : 147 W
 Fuse protection : 10 A
 Voltage : 220-240 V
 Frequency : 50; 60 Hz
 Plug type : GB plug
 Installation typology : Wall-mounted

Optional accessories

Z51AII1X6	Clean Air Plus recirculation kit
Z51AIROX0	Long Life recirculation kit (chimless)
Z51AISOX0	Long Life recirculation kit
Z51AIV1X6	Clean Air Plus recirc. kit (chimless)
Z51AXK0N0	Chimney extension 1000 mm
Z51AXL0N0	Chimney extension 1500 mm



4 242004 230786

N 90, wall-mounted cooker hood, 90 cm, clear
glass black printed
D951MT1NOB



COOKING PASSION SINCE 1877

Features

Key performance features:

- Energy Efficiency Class: A (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 431 m³/h
Intensive 714 m³/h
- Noise max. Normal Level: 53 dB*

Features

- Ambient light
- Touch control
- LED display
- 3 power levels and 2 intensive settings
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- softLight with dimmer function
- Efficient BLDC-technology
- Noise reduction function
- Interval operation
- Automatic after running (10 minutes)
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- easy to clean Inner frame
- For wall mounted installation
- Rim ventilation

Design

- Chimney hood
- Electronic controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Installation system: Wall fixing inclined/flat/cube
- Extraction rate according to EN 61591 max. 431 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 53 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 53 dB(A) re 1 pW
Intensive: 65 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 53 dB (A) re 1pW
- Extraction rate in recirculation mode:
Max. normal use: 410 m³/h
Intensive: 632 m³/h
- Noise levels in recirculation mode:
Max. normal use: 63 dB(A) re 1 pW
Intensive: 74 dB(A) re 1 pW
- Power rating: 147 W
- Light Intensity: 238 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 930-1200 x 895 x 502 mm
- Dimensions recirculating (HxWxD): 990-1260 x 895 x 502 mm
- Dimensions recirculating with CleanAir module (HxWxD):
1120 x 895 x 502 mm - mounting with outer chimney
1190-1460 x 895 x 502 mm - mounting with telescopic chimney
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 34.6 kWh/year*

Optional accessories

- Recirculating kit Z50XXPOX0

* In accordance with the EU-Regulation No 65/2014

N 90, wall-mounted cooker hood, 90 cm, clear
glass black printed
D951MT1N0B

Dimensioned drawings

