


N 90, WALL-MOUNTED COOKER HOOD, 90 CM,  
CLEAR GLASS BLACK PRINTED  
D961KW1SOB



A+



The design hood with an inclined front and high power ensures headroom while cooking.

- ✓ Ambient Light – Individualized lighting with endless colour shades via Home Connect.
- ✓ Fully Automatic Hood – Takes control as soon as you switch on the hob.
- ✓ Cooktop-based Hood Control – Adjust your hood’s extraction level and lighting.
- ✓ Efficient Drive Motor – Quiet and energy-efficient hood motor for a calmer kitchen.

Features

Technical Data

Typology: .....Wall-mounted  
 Length electrical supply cord: ..... 130.0 cm  
 Height of the appliance: ..... 323 mm  
 Minimum distance above an electric hob: ..... 450 mm  
 Minimum distance above a gas hob: ..... 650 mm  
 Net weight: ..... 25.9 kg  
 Type of control: ..... Electronic  
 Number of speed settings: ..... 3-stage + 2 intensive  
 Maximum output air extraction: ..... 468 m<sup>3</sup>/h  
 Boost position output recirculating: ..... 703.0 m<sup>3</sup>/h  
 Maximum output recirculating air: ..... 459 m<sup>3</sup>/h  
 Boost position air extraction: ..... 837 m<sup>3</sup>/h  
 Maximum Air flow: ..... 468 m<sup>3</sup>/h  
 Number of lights: ..... 2  
 Noise level: ..... 55 dB(A) re 1 pW  
 Diameter of air outlet: ..... 120 / 150 mm  
 Grease filter material: ..... Washable aluminium  
 EAN code: ..... 4242004209584  
 Connection Rating: ..... 170 W  
 Fuse protection: ..... 10 A  
 Voltage: ..... 220-240 V  
 Frequency: ..... 60; 50 Hz  
 Plug type: ..... GB plug  
 Installation typology: .....Wall-mounted  
 Delay Shut off modes: ..... 10 min

Optional accessories

Z51AXK0N0	Chimney extension 1000 mm
Z51AXL0N0	Chimney extension 1500 mm
Z53XXB1X6	Clean Air Plus odor filter (replacement)
Z91AXE1S1	Chimney standard black
Z50XXPOX0	Long Life odor filter (replacement)
Z51AIB1X6	Clean Air Plus odor filter (replacement)
Z51AII1X6	Clean Air Plus recirculation kit
Z51AIROX0	Long Life recirculation kit (chimless)
Z51AIS0X0	Long Life recirculation kit
Z51AIV1X6	Clean Air Plus recirc. kit (chimless)
Z51AXC1N6	Clean Air Plus recirc. kit external



N 90, WALL-MOUNTED COOKER HOOD, 90 CM,  
CLEAR GLASS BLACK PRINTED  
D96IKW1SOB

Features

**Key performance features:**

- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591  $\varnothing$  15 cm:
- max. Normal use 467 m<sup>3</sup>/h
- Intensive 837 m<sup>3</sup>/h
- Noise max. Normal Level: 55 dB\*
- Remote Monitoring and Control for connected home appliances and operation via smartphone or tablet (only in countries where Home Connect service is available)
- The Home Connect functionality can be extended by integrating numerous applications from external cooperation partners (partnerships)
- Voice Control enabled via popular voice assistants (only in countries where this service is available)

**Features**

- Hob-Hood control (with Wi-Fi enabled hob)
- Climate Control Sensor
- Ambient light
- Touch control
- LED display
- 3 power levels and 2 intensive settings
- Noise reduction function
- 2 x 3w LED Light
- Colour Temperature: 3500 K
- softLight with dimmer function
- Efficient BLDC-technology
- Interval operation
- Automatic after running (10 minutes)
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- Additional noise insulation
- easy to clean Inner frame
- For wall mounted installation
- Rim ventilation

**Design**

- Chimney hood
- Electronic controls

**Performance/technical information**

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Installation system: Wall fixing inclined/flat/cube
- Extraction rate according to EN 61591 max. 467 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 55 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 55 dB(A) re 1 pW
- Intensive: 67 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 55 dB (A) re 1 pW

- Power rating: 170 W
- Light Intensity: 519 lux
- Electrical cable length 1.3 m
- Diameter pipe  $\varnothing$  150 mm ( $\varnothing$  120 mm enclosed)
- Dimensions exhaust air (HxWxD): 928-1198 x 890 x 545 mm
- Dimensions recirculating (HxWxD): 988-1258 x 890 x 545 mm
- Dimensions recirculating with CleanAir module (HxWxD):
- 1118 x 890 x 545 mm - mounting with outer chimney
- 1188-1458 x 890 x 545 mm - mounting with telescopic chimney
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*
- Average Energy Consumption: 31.5 kWh/year\*

**Optional accessories**

- Recirculating kit Z51AXK0N0

\* In accordance with the EU-Regulation No 65/2014

N 90, WALL-MOUNTED COOKER HOOD, 90 CM,  
CLEAR GLASS BLACK PRINTED  
D96IKW1SOB

Dimensioned drawings

