

N 50, BUILT-UNDER FREEZER, 82 X 59.8 CM, FLAT HINGE
G4344XFF0G



The built-in freezer with temperature rise alarm and superfreeze function.

√ Super Freeze – Lowers the temperature temporarily to prevent frozen goods from warming up as new items are added.

Energy Efficiency Class:F
 Average annual energy consumption in kilowatt hour per year (kWh/a): 224 kWh/annum
 Sum of volume of frozen compartments: 106 l
 Airborne acoustical noise emissions : 38 dB(A) re 1pW
 Airborne acoustical noise emission class: C
 Thermometer freeze section: Analog
 Light: No
 Product category: Upright freezer
 Built-in / Free-standing: Built-in
 Door panel options: Possible but accessory
 Frost free system:No
 Height of the appliance: 820 mm
 Width of the appliance: 598 mm
 Depth: 548 mm
 Dimensions of the packed product (HxWxD): . 890 x 670 x 620 mm
 Net weight: 36.7 kg
 Gross weight: 39.6 kg
 Connection Rating: 90 W
 Fuse protection: 13 A
 Frequency: 50 Hz
 Length electrical supply cord: 230.0 cm
 Door hinge:Right reversible
 Defrost process: manual
 Warning signal / malfunction: Both visual and audible
 Door lock: No
 Number of drawers/baskets (Stck): 3
 Number of freezing flaps (Stck):0
 EAN code:4242004237693
 Brand:Neff
 Product name / Commercial code: G4344XFF0G
 Product category: Upright freezer
 Included accessories: 1 x ice cube tray

1 x ice cube tray

KU1213Z0 Attachment door, stainless steel



N 50, BUILT-UNDER FREEZER, 82 X 59.8 CM, FLAT
HINGE
G4344XFF0G

Functions

- Fully Integrated

Design features

- Mechanical control
- Temperature indicator on inside of door
- 1 compressor/1 cooling circuit
- SuperFreeze function with automatic deactivation
- Freezer malfunction warning signal: Optic and acoustic Warning System

Food freshness system

- 3 freezer drawers
- 1 ice cube tray with lid
- Right hinged door, reversible
- Ventilation through plinth
- Variable plinth adaption
- Height adjustable feet in the front
- Connection value 90 W
- 220 - 240 V

Dimension and installation

- Dimensions: 82 cm H x 59.8 cm W x 54.8 cm D
- Niche Dimensions: 82 cm H x 60 cm W x 55 cm D

Key features - Freezer section

- G4344XFF0G

Included accessories

- KU1213Z0

Design features

Dimension and installation


Additional features

Performance and Consumption

- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.
- EU19_EEK_D: F
- Total Volume : 106 l
- Net 4* compartment volume : 106 l
- Freezing capacity 24h : 7.4 kg
- Annual Energy Consumption: 224 kWh/a
- Climate Class: SN-T
- Temperature rise time : EU19_Temperature rise time_D: 10 H


N 50, BUILT-UNDER FREEZER, 82 X 59.8 CM, FLAT HINGE
G4344XFF0G

measurements in mm
Recommended gap dimensions for flat hinges



| F | R | X |
|-------|-----|-----|
| 16-19 | 0-3 | 2.5 |
| 20 | 0-1 | 3 |
| | 2-3 | 2.5 |
| 21 | 0-1 | 3 |
| | 2-3 | 2.5 |
| 22 | 0 | 4 |
| | 1 | 3.5 |
| | 2-3 | 3 |

The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units.



Maximal permissible weight of the unit fronts

Fitted unit fronts that exceed the permissible weight may cause damage and result in functional impairment of the hinges

Δ Weight

A: Appliance door height including hinges in mm

B: Undamped hinge, unit front in kg

C: Damped hinge, unit front in kg

D: Additional possible load in kg with heavy load kit

| A | B | C | D |
|-----------|----|----|-----------|
| 1500-1750 | 22 | 22 | B+5 / C+5 |
| 720-1400 | 19 | 19 | |
| A1 | 15 | 19 | |
| A2 | 15 | 19 | |

