

N 50, ISLAND COOKER HOOD, 90 CM, CLEAR GLASS 189EH52N0B



- ✓ Efficient Drive Motor – Quiet and energy-efficient hood motor for a calmer kitchen.
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ Dimmer Function – easily dim the light according to your mood with the touch of a button
- ✓ Interval Ventilation – automatically ventilates every hour for crisp, clean air
- ✓ Automatic After-running – ventilation continues for several minutes after you turn it off

Z50XXP0X0	Long Life odor filter (replacement)
Z5101X1	Standard odor filter (replacement)
Z5105X5	Standard recirculation kit
Z5170X1	CleanAir active carbon filter spare part
Z5280X0	CleanAir Recirculation Kit
Z5908N1	Chimney extension 1100 mm
Z5911X0	Adapter for roof inclination left/right
Z5913X0	Adapter for roof inclination front/back
Z5918N1	Chimney extension 1600 mm
Z5920N0	Extension for mounting kit 500 mm
Z5922N0	Extension for mounting kit 1000 mm

Typology: Island/Ceiling
Length electrical supply cord: 130.0 cm
Height of the chimney: 699-879/699-999 mm
Height of the appliance: 52 mm
Minimum distance above an electric hob: 550 mm
Minimum distance above a gas hob: 650 mm
Net weight: 35.1 kg
Type of control: Electronic
Number of speed settings: 3-stage + 2 intensive
Maximum output air extraction: 430 m³/h
Boost position output recirculating: 350.0 m³/h
Maximum output recirculating air: 290 m³/h
Boost position air extraction: 670 m³/h
Maximum Air flow: 430 m³/h
Number of lights: 4
Noise level: 57 dB(A) re 1pW
Diameter of air outlet: 150 / 120 mm
Grease filter material: Washable aluminium
EAN code: 4242004174622
Connection Rating: 142 W
Fuse protection: 10 A
Voltage: 220-240 V
Frequency: 50; 60 Hz
Plug type: GB plug
Installation typology: Island



N 50, ISLAND COOKER HOOD, 90 CM, CLEAR GLASS
189EH52N0B

Special features

- 7 segment LED display
- Interval operation

Features

- 4 x LED lights
- SoftLight with dimmer
- 1 metal grease filter cassette
- SoftLight with dimmer function

Design

- 90 cm wide
- For ceiling mounted installation
- Glass canopy
- Clear glass
- Soft touch control for extractor speeds and light
- Height adjustable

Performance/technical information

- Suitable for ducted extraction and recirculation
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 430 m³/h
 - Intensive 670 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 57 dB (A) re 1 pW (43 dB (A) re 20 µPa sound pressure)
- 3 power levels and 2 intensive settings
- Automatic intensive revert (6mins)
- Automatic revert setting

N 50, ISLAND COOKER HOOD, 90 CM, CLEAR GLASS
189EH52NOB

