

N 70, ISLAND COOKER HOOD, 90 CM, STAINLESS
STEEL
I96BMP5N0B



The coordinating and stylish Neff box hood is modern in design and keeps up with your cooking.

- ✓ Efficient Drive Motor – Quiet and energy-efficient hood motor for a calmer kitchen.
- ✓ Touch Control: an integrated flat surface control panel for smooth operation with a fingerswipe.
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ Dimmer Function – easily dim the light according to your mood with the touch of a button

Z50XP0X0	Long Life odor filter (replacement)
Z52CBD2X1	Long Life recirculation kit external
Z52CBI2X4	Clean Air Standard recirculation kit
Z52CXC2N6	Clean Air Plus recirc. kit external
Z53CBB2X4	Clean Air Standard odor filter (repl.)
Z53XXB1X6	Clean Air Plus odor filter (replacement)
Z5909N1	Chimney extension 1100 mm
Z5912X0	Adapter for roof inclination left/right
Z5914X0	Adapter for roof inclination front/back
Z5919N1	Chimney extension 1600 mm
Z5921N0	Extension for mounting kit 500 mm
Z5923N0	Extension for mounting kit 1000 mm

Typology: Island/Ceiling
Length electrical supply cord: 130.0 cm
Height of the chimney: 698-878/698-998 mm
Height of the appliance: 46 mm
Minimum distance above an electric hob: 550 mm
Minimum distance above a gas hob: 650 mm
Net weight: 28.8 kg
Type of control: Electronic
Number of speed settings: 3-stage + 2 intensive
Maximum output air extraction: 445 m³/h
Boost position output recirculating: 457 m³/h
Maximum output recirculating air: 353 m³/h
Boost position air extraction: 867 m³/h
Maximum Air flow: 445 m³/h
Number of lights: 4
Noise level: 54 dB(A) re 1pW
Diameter of air outlet: 120 / 150 mm
Grease filter material: Washable stainless steel
EAN code: 4242004234982
Connection Rating: 166 W
Fuse protection: 10 A
Voltage: 220-240 V
Frequency: 50; 60 Hz
Plug type: GB plug
Installation typology: Island



N 70, ISLAND COOKER HOOD, 90 CM, STAINLESS STEEL I96BMP5NOB

Key performance features:

- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 445 m³/h
- Intensive 867 m³/h
- Noise max. Normal Level: 54 dB*

Features

- Touch control
- 3 power levels and 2 intensive settings
- 4 x 1.5w LED Light
- softLight with dimmer function
- Efficient BLDC-technology
- Interval operation
- Automatic after running (10 minutes)
- Automatic intensive revert (6mins)
- 3 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
- Noise reduction function
- Additional noise insulation
- easy to clean Inner frame

Design

- Island chimney hood
- For ceiling mounted installation
- Electronic controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 max. 445 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 54 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 54 dB(A) re 1 pW
- Intensive: 69 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 54 dB (A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode: Max. normal use: 353 m³/h
- Intensive: 457 m³/h
- Noise level in recirculation mode: Max. normal use: 67 dB(A) re 1 pW
- Intensive: 71 dB(A) re 1 pW
- Power rating: 166 W
- Light Intensity: 423 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m

- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Dimensions recirculating with CleanAir module (HxWxD): 812-1044 x 898 x 600 mm
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 31.9 kWh/year*

Optional accessories

- Recirculating kit Z50XP0X0

* In accordance with the EU-Regulation No 65/2014

N 70, ISLAND COOKER HOOD, 90 CM, STAINLESS
STEEL
I96BMP5NOB

