

N 50, BUILT-UNDER DOUBLE OVEN J1ACE2HNOB







Included accessories

2 x combination grid, 1 x universal pan

Optional accessories

Z11AB15A0 Baking tray, non-stick ceramic coated, Z11AU15A0 Universal pan, non-stick ceramic coated, Z11CR10X0 Baking and roasting grid (standard), Z11TI15X0 Cliprails, Z12CB10A0 Baking tray, enamelled, Z12CM10A0 Moussaka pan, enamelled, Z12CP10A0 Pizza pan, enamelled, Z12CU10A0 Multipurpose pan, enamelled, Z1365WX0 Wireless food thermometer, Z13CR10X0 Baking and roasting grid (steam), Z1608BX0 Full ext rails, level independent, Z1655CA0 Air Fry & Grill tray, Z1913X0 Baking Stone

Built under double oven - twice as flexible, twice as fast - bake or roast multiple dishes at the same time.

- $\sqrt{}$ EasyClean this special cleaning aid provides uncomplicated, energy-saving cleaning of the oven interior.
- $\sqrt{\,}$ LCD-Display simple, straightforward with large characters for clear reading
- $\sqrt{\,}$ Cliprails Place dishes exactly where you want them in your oven

Features

Technical Data		
Built-in / Free-standing:	Built-in	
Integrated Cleaning system:	No	
Dimensions:	. 717x594x550 mm	
Dimensions of the packed product (HxWxD):	790x660x690 mm	
Control Panel Material:	Glass	
Door Material:	Glass	
Net weight:	47.3 kg	
Usable volume (of cavity) - cavity 1:	47	
Cooking method: Full width grill, Ho	tair gentle, Hot Air,	
Conventional heat, Pizza setting, Hot air grilling		
EAN code:	4242004221982	
Energy efficiency rating:	A	
Energy consumption per cycle conventional (20	110/30/EC): 0.84	
kWh/cycle		
Energy consumption per cycle forced air conve	ction	
(2010/30/EC):	0.71 kWh/cycle	
Energy efficiency class (2010/30/EC) - cavity 2	: B	
Energy consumption per cycle conventional - ca	*	
(2010/30/EC):		
Energy efficiency index (2010/30/EC):	94.7 %	
Energy efficiency index cavity 2 (2010/30/EC):	120.3 %	
Connection Rating:	5300 W	
Fuse protection:	25 A	
Voltage:	220-240 V	
Frequency:	50 Hz	
Plug type:	, ,	
(electrical connection by electrician), fixed connection (electrical		
connection by electrician)		
Included accessories:2 x combination gr	id, 1 x universal pan	





N 50, BUILT-UNDER DOUBLE OVEN J1ACE2HNOB

Features

• LCD Display (White)

Features

- Control panel lock
- Interior halogen light
- Cavity volume: 34 Litre
- Door hinge small cavity: bottom
- Cavity (inner surface) top: Enamel grey
- EasyClean
- Full glass inner door
- 1 Clip rail, Stop function
- Cavity (inner surface) bottom: enamel anthracite
- Door hinge big cavity: Drop down door

Top oven additional features

- Oven with 4 heating methods: Top/bottom heat, Full surface grill, Small area grill, Bottom heat
- Temperature range 50 °C 275 °C

Main oven additional features

• 2 x combination grid, 1 x universal pan


Performance/technical information

- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 717 mm x 594 mm x 550 mm
- Ventilation requirements please refer to the installation manual prior to fitting



N 50, BUILT-UNDER DOUBLE OVEN J1ACE2HNOB

Dimensioned drawings



measurements in mm

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	39	40
Full-surface induction hob	49	50
Gas hob	29	40
Electric hob	29	32

