

N 50, 82 X 60 CM, FLAT HINGE K4316XFF0G













1 x egg tray

KSGG0MZ0 Butter box

KU1213Z0 Attachment door, stainless steel

This undercounter refrigerator keeps fruit and vegetables at their

- $\sqrt{\mbox{ Fresh Safe}}$ Fridge drawer for dedicated fresh fruit and veg storage.
- $\sqrt{\mbox{ Adjustable Glass Shelves}}$ Height adjustable shelves create the space you need for inspiring dishes in your fridge
- $\ensuremath{\sqrt{}}$ Our safety glass shelves happily shoulder generous loads of delicacies in your fridge
- $\sqrt{\mbox{ LED Light}}$ Pleasant illumination for the entire fridge, with long-life LEDs.

Energy Efficiency Class:
Average annual energy consumption in kilowatt hour per year (kWh/a):
(kWh/a):
Sum of volume of chill compartments:
Sum of volume of chill compartments:
Airborne acoustical noise emission class:
Built-in / Free-standing: Built-in Door panel options: Possible but accessory Height: 820 mm Width of the appliance: 598 mm Depth: 548 mm Min. required niche size for installation (HxWxD): .820 x 600 x 550 mm Net weight: 33.9 kg
Door panel options:
accessory Height:
Height: 820 mm Width of the appliance: 598 mm Depth: 548 mm Min. required niche size for installation (HxWxD): .820 x 600 x 550 mm Net weight: 33.9 kg
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$
Depth:
Min. required niche size for installation (HxWxD): $.820 \times 600 \times 550$ mm Net weight:
mm Net weight:
Net weight:
<u> </u>
Connection Rating 90 W
Fuse protection:
Door hinge:
Voltage:
Frequency:
Length electrical supply cord: 230.0 cm
Number of compressors:
Interior ventilator: No
Reversible Door Hinge: Yes
Number of Adjustable Shelves in fridge compartment:
Shelves for Bottles: Yes
EAN code:
Brand: Neff
Product name / Commercial code:
Product category:
Frost free system:
Installation typology:
Included accessories:





N 50, 82 X 60 CM, FLAT HINGE K4316XFF0G

Functions

- Ventilation through plinth
- Easy clean interior

Design features

- Mechanical control
- Single cooling circuit
- Automatic defrost fridge

Design features

- 3 safety glass shelves in fridge compartment of which 2 are height adjustable
- Full width pull out drawer
- 1 removable door storage compartments.
- Bottle holder in x-deep door tray
- Bright interior LED fridge light

Freshness System

• 2 vegetable/salad containers

Key features - Fridge section

- Height adjustable feet in the front
- Right hinged door, reversible
- Connection value 90 W
- 220 240 V

Dimension and installation

- • Niche Dimensions: 82 cm H x 60 cm W x 55 cm D
- Dimensions: 82 cm H \times 59.8 cm W \times 54.8 cm D

Key features - Feezer section

• K4316XFF0G

Included accessories

• KSGG0MZ0, KU1213Z0


Performance and Consumption

- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.
- EU19_EEK_D: F
 Total Volume : 137 I
- Annual Energy Consumption: 114 kWh/a
- Climate Class: SN-STNoise Level : 38 dB




N 50, 82 X 60 CM, FLAT HINGE K4316XFF0G

measurements in mm Recommended gap dimensions for flat hinges



F	R	X	
16-19	0-3	2.5	
20	0-1	3	
	2-3	2.5	
21	0-1	3	
	2-3	2.5	
22	0	4	
	1	3.5	
	2-3	3	


The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units.



* variable base/substructure height

Space for electrical connection next to the appliance on the left or right-hand side. Ventilation space in the base.

measurements in mm



Maximal permissible weight of the unit fronts

Fitted unit fronts that exceed the permissible weight may cause damage and result in functional impairment of the hinges å Weight A: Appliance door height including hinges in mm

B: Undamped hinge, unit front in kg

C: Damped hinge, unit front in kg

D: Additional possible load in kg with heavy load kit

Α	В	С	D
1500-1750	22	22	
720-1400	19	19	B+5 / C+5
A1	15	19	
Δ2	15	10	