N 50, built-in fridge-freezer with freezer at bottom, 177.2 x 54.1 cm, flat hinge KI5852FF0G
















- $\sqrt{\mbox{ Fresh Safe}}$ Fridge drawer for flexible storage of your fresh fruit and vegetables.
- $\sqrt{\ }$ LowFrost: Reduces frost in the freezer compartment for faster defrosting.
- $\sqrt{\,}$ Adjustable Glass Shelves Height adjustable shelves create the space you need for inspiring dishes in your fridge
- $\sqrt{\,}$ Our safety glass shelves happily shoulder generous loads of delicacies in your fridge
- $\sqrt{\,}$ Vario Zone Individualize your drawers with various loading options to create the optimal fit for frozen goodies

Feature:

Technical Data

Energy Efficiency Class: F

Average annual energy consumption in kilowatt hour per year (kWh/

a): 285 kWh/annum

Sum of volume of frozen compartments : 102 $\,$ I Sum of volume of chill compartments : 159 $\,$ I

Airborne acoustical noise emissions : 38 dB(A) re 1 pW

Airborne acoustical noise emission class : C

Built-in / Free-standing : Built-in Door panel options : Not possible Width of the appliance : 541 mm

Depth: 545 mm

Required niche size for installation (HxWxD) : $1775.0 \times 560 \times 550$

mm

Net weight: 65.6 kg Connection Rating: 90 W Fuse protection: 13 A Door hinge: Right reversible Voltage: 220-240 V Frequency: 50 Hz

Approval certificates : CE, VDE Length electrical supply cord : 230 cm

Storage Period in Event of Power Failure (h): 10 h

Number of compressors : 1

Number of independent cooling systems : 1

Interior ventilator : No Reversible Door Hinge : Yes

 $\label{prop:number} \mbox{Number of Adjustable Shelves in fridge compartment}: 3$

Shelves for Bottles : No Frost free system : No

Installation typology : Full-integrated Type of hinge : Flush-folding





N 50, built-in fridge-freezer with freezer at bottom, 177.2 x 54.1 cm, flat hinge KI5852FF0G

Feature

Functions

• Bright interior LED fridge light

Design features

- Electronic control (LED chain)
- vitaControl constant temperature by intelligent sensor technology - Constant temperature control by intelligent sensor technology
- SuperFreeze function with automatic deactivation
- Single cooling circuit

Design features

- 4 safety glass shelves in fridge compartment of which 3 are height adjustable
- 4 door bins

Freshness System

• 1 FreshSafe drawer- The ideal place to store your fruit and vegetables safely.

Food freshness system

- lowFrost freezer
- Removeable safety glass shelves in freezer
- 4 transparent freezer drawers, 1 bigbox

Dimension and installation

- Dimensions: 177.2 cm H x 54.1 cm W x 54.5 cm D
- \bullet Niche Dimensions: 177.5 cm H x 56 cm W x 55 cm D

Key features - Fridge section

- Right hinged door, reversible
- Connection value 90 W
- 220 240 V

Key features - Feezer section

- 2 x egg tray, 2 x ice cube tray
- bottle holder in door tray
- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.

Performance and Consumption

- EU19_EEK_D: F
- Total Volume : 261 l
- Net Fridge Volume : 159 l
- Net Freezer Volume: 102 l
- Net 4* compartment volume : 102 l
- Freezing capacity 24h : 4.6 kg
- Annual Energy Consumption: 285 kWh/a
- Climate Class: SN-ST
- Noise Level : 38 dB
- \bullet Temperature rise time : EU19_Temperature rise time_D: 10 H



N 50, built-in fridge-freezer with freezer at bottom, 177.2 x 54.1 cm, flat hinge KI5852FF0G

COOKING PASSION SINCE 1877

Dimensioned drawings measurements in mm min. 40 Front panel Recommended gap dimensions for flat hinges overhang 868+B (min.) 894+B (max.)-16-19 0-3 2.5 0-1 3 2.5 2-3 0-1 21 3 -900+A 4-2-3 874+A -(min.) • 22 0 4 Lower edge of front panel The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units. The specified unit door dimensions are valid for a door gap of 4 mm. measurements in mm Air outlet min. 200 cm² min. 2200 560 recommended min. 550 1772+8 Ventilation space in the base min. 200 cm² measurements in mm 1772 841 865 874 904 measurements