

*N 70, BUILT-IN FRIDGE-FREEZER WITH FREEZER
AT BOTTOM, 177.2 X 55.8 CM, FLAT HINGE
K16863FE0G*



Optional accessories

KS9E0FZ0	Package Neff FlexCooling
KSGG0MZ0	Butter box
Z10020	Bottle Rack

This built-in combination refrigerator/freezer with LowFrost and LED interior lighting and food freshness systems keeps foods fresher for longer.

- ✓ Fresh Safe 2 – Ideal storage for fruit and veg.
- ✓ Low Frost – Reduces frost in the freezer compartment for faster defrosting
- ✓ Easy Access Shelf – Slides out for easier access to items in your fridge.
- ✓ Vario Shelf – The glass shelf that can be divided, with one half stored beneath the other, for flexible configurations.
- ✓ Adjustable Glass Shelves – Height adjustable shelves create the space you need for inspiring dishes in your fridge

Features

Technical Data

Energy Efficiency Class ¹ :	E
Average annual energy consumption in kilowatt hour per year (kWh/a):	219 kWh/annum
Sum of volume of frozen compartments:	74 l
Sum of volume of chill compartments:	192 l
Airborne acoustical noise emissions :	36 dB(A) re 1pW
Airborne acoustical noise emission class:	C
Built-in / Free-standing:	Built-in
Door panel options:	Not possible
Height:	1772 mm
Width of the appliance:	558 mm
Depth:	545 mm
Required niche size for installation (HxWxD):	...1775x560x550 mm
Net weight:	62.6 kg
EAN code:	4242004246282
Connection Rating:	90 W
Fuse protection:	13 A
Door hinge:	Right reversible
Voltage:	220-240 V
Frequency:	50 Hz
Length electrical supply cord:	230.0 cm
Number of compressors:	1
Number of independent cooling systems:	2
Interior ventilator:	No
Reversible Door Hinge:	Yes
Number of Adjustable Shelves in fridge compartment:	4
Shelves for Bottles:	Yes
Frost free system:	Not applicable
Installation typology:	Full-integrated



¹ Scale of Energy Efficiency Classes from A to G

*N 70, BUILT-IN FRIDGE-FREEZER WITH FREEZER
AT BOTTOM, 177.2 X 55.8 CM, FLAT HINGE
KI6863FE0G*

Features

Functions

- Bright interior LED fridge light
- Interior design with metal applications

Design features

- Touchcontrol- Electronic - Electronic controls for fridge and freezer
- vitaControl - constant temperature by intelligent sensor technology - Constant temperature control by intelligent sensor technology
- Two separate cooling circuits allow independent temperature control and prevents the transference of humidity between the fridge and freezer cavity
- SuperCool function with automatic deactivation
- SuperFreeze functions with automatic deactivation
- Holiday mode - saves energy when you're away a longer period of time
- Acoustic door open warning indicator
- Freezer malfunction warning signal: optical and acoustical

Design features

- 4 safety glass shelves (4 height adjustable)
- 5 door trays, including 1x dairy compartment
- BottleFlex Shelf

Freshness System

- 1 FreshSafe 2 drawer; High humidity retains nutrients up to twice as long

Food freshness system

- lowFrost freezer
- Removeable safety glass shelves in freezer
- 3 transparent freezer drawers, 1 bigbox

Dimension and installation

- Dimensions: 177.2 cm H x 55.8 cm W x 54.5 cm D
- Niche Dimensions: 177.5 cm H x 56 cm W x 55 cm D

Key features - Fridge section

- Right hinged door, reversible
- Connection value 90 W
- 220 - 240 V

Key features - Freezer section

- KI6863FE0G
- bottle holder in door tray

Country Specific Options

- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.

Design features

Dimension and installation

Additional features





Performance and Consumption

- EU19_EEK_D: E


- Total Volume : 266 l
- Net Fridge Volume : 192 l
- Net Freezer Volume : 74 l
- Freezing capacity 24h : 7 kg
- Annual Energy Consumption: 219 kWh/a
- Climate Class: SN-ST
- Noise Level : 36 dB
- Temperature rise time : EU19_Temperature rise time_D: 9 H

*N 70, BUILT-IN FRIDGE-FREEZER WITH FREEZER
AT BOTTOM, 177.2 X 55.8 CM, FLAT HINGE
K16863FE0G*

Dimensioned drawings




Dimensioned drawings



The specified unit door dimensions are valid for a door gap of 4 mm.
measurements in mm

measurements in mm
Recommended gap dimensions for flat hinges



F	R	X
16-19	0-3	2.5
20	0-1	3
	2-3	2.5
21	0-1	3
	2-3	2.5
22	0	4
	1	3.5
	2-3	3

The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units.