

# N 90, BUILT-IN FRIDGE, 177.2 X 55.8 CM, SOFT CLOSE FLAT HINGE KI8816DE1











### Included accessories

1 x bottle holder in door tray

## Optional accessories

KS0B0SZ0 Heavy-duty hinge support KS1860Z0 Wire Shelf The built-in fridge with FreshSafe 3 and BottleFlex Shelf keeps food fresher for longer and offers a lot of extra storage options.

- $\sqrt{\mbox{ Fresh Safe 3}}$  Climate-controlled drawers for optimal fresh food storage.
- $\sqrt{\mbox{ Easy Access Shelf}}$  Slides out for easier access to items in your fridge.
- $\sqrt{\rm Vario~Shelf}$  The glass shelf that can be divided, with one half stored beneath the other, for flexible configurations.
- $\sqrt{\,}$  Adjustable Glass Shelves Height adjustable shelves create the space you need for inspiring dishes in your fridge
- $\sqrt{\,}$  Our safety glass shelves happily shoulder generous loads of delicacies in your fridge

### Features

Technical Data	
Energy Efficiency Class <sup>1</sup> :E	
Average annual energy consumption in kilowatt hour per year	
(kWh/a):	
Sum of volume of frozen compartments:	
'	
Sum of volume of chill compartments:	
Airborne acoustical noise emissions :	
Airborne acoustical noise emission class:	
Built-in / Free-standing:	
Door panel options:	
Height:	
Width of the appliance:	
Depth:	
Required niche size for installation (HxWxD):1775x560x550 mm	
·	
Net weight: 65.9 kg	
Connection Rating: 90 W	
Fuse protection:	
Door hinge:Right reversible	
Voltage:	
Frequency:50 Hz	
Length electrical supply cord:	
Number of compressors:1	
Number of independent cooling systems:	
Interior ventilator:	
Reversible Door Hinge: Yes	
Number of Adjustable Shelves in fridge compartment:	
Shelves for Bottles: Yes	
EAN code:	
Brand: Neff	
Product name / Commercial code:	
Product category:	
Frost free system:	
Installation typology:Full-integrated	
Included accessories: 1 x bottle holder in door tray	
4 2 4 2 0 0 4 2 6 2 6 5 7	•

<sup>&</sup>lt;sup>1</sup> Scale of Energy Efficiency Classes from A to G



# N 90, BUILT-IN FRIDGE, 177.2 X 55.8 CM, SOFT CLOSE FLAT HINGE KI8816DE1

#### Features

• Built-in fridge

• Easy Installation

#### Performance and Consumption

• EU19\_EEK\_D: E

• Total Volume : 289 l

Net Fridge Volume : 289 INet Freezer Volume : 0 I

• Annual Energy Consumption: 150 kWh/a

• Climate Class: SN-ST

• EU19\_Fast freezer facility\_D: no

• Noise Level: 37 dB

#### **Functions**

• LED with Soft Start

• Interior design with metal applications

#### Design features

- Fixed hinge, SoftClose door dampens door movement, for smooth and effortless closure
- LED Electronic control
- Automatic defrost fridge
- SuperCool function with automatic deactivation
- Acoustic door open warning indicator

### Design features

- 7 safety glass shelves of which Non-adjustable bottom shelf, Easy Access shelf
- BottleFlex Shelf
- 9 door trays, including 0x dairy compartment

#### Freshness System

- Capacity in 0° C section: 83 l
- 1 FreshSafe 3 0°C drawer with humidity control for optimal freshness; food stays fresh for longer due to two climate zones.
- ullet 2 FreshSafe 3 0°C drawers for optimal freshness; food stays fresh for longer due to two climate zones.

### Dimension and installation

- Dimensions: 177.2 cm H  $\times$  55.8 cm W  $\times$  54.5 cm D
- Niche Dimensions: 177.5 cm H x 56 cm W x 55 cm D

### Key features - Fridge section

- Right hinged door, reversible
- Connection value 90 W
- 220 240 V

### Key features - Feezer section

• 1 x bottle holder in door tray

## Included accessories

• KS0B0SZ0, KS1860Z0

# Country Specific Options

• Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.


#### Design features

Dimension and installation

Additional features




# N 90, BUILT-IN FRIDGE, 177.2 X 55.8 CM, SOFT CLOSE FLAT HINGE KI8816DE1





## Dimensioned drawings


Maximal permissible weight of the unit fronts



Fitted kitchen unit doors that exceed the permissible weight may cause damage and result in functional impairment of the hinges.

of appliance door		damped hinge,
Hinges in mm:	Door in kg:	Door in kg:
1500-1750	22	22

measurements in mm Recommended gap dimensions for flat hinges



F	R	X	
16-19	0-3	2.5	
20	0-1	3	
	2-3	2.5	
21	0-1	3	
	2-3	2.5	
22	0	4	
	1	3.5	
	2-3	3	
-			

The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units.